

HUDY PERSONAL RACING DISPL

#107850

- FEATURES Compact all-in-one data center for RC car drivers Indicators for:
 > time > temperature > humidity > date > alarm
 - Environment comfort display:
 - > comfortable > wet > dry
 Temperature range: 0-50°C (32-120°F)

 - Temperature shown in °C and °F Max & Min temperature and humidity memory
- Max & Min temperature and humidity memory
 Time indicator in 12hr or 24hr clock
 Extra features: > date > alarm clock
 Temperature accuracy: ± 1.0°C (±1.8°F)
 Temperature resolution: 0.1°C (0.1°F)
 Humidity measuring range: 10–90% RH
 Humidity accuracy: ±5% (40–80%) other ±8%
 Power: AAA 1.5V battery (included)

BASIC FUNCTIONS

calendar

MODE:

adjust the value of item, alarm on/off, date indicatation

clock/alarm switch, setting clock & alarm &

MEMO: indicates MAX/MIN temperature and humidity °C / °F: °C / °F temperature switch

RESET: clears all settings & memory back to their original states (at rear)

°C / °F: Switches between °C and °F (at rear)

- TIME AND DATE SETTING Press and hold **[MODE]** for 3 seconds until the minute starts flashing; press **[ADJ]** to adjust the Press
 - minutes Press [MODE] again until the hour
- press [ADJ] to adjust the hour. Press [MODE] again to set the clock mode; press [ADJ] to select 12hr mode (US time) or 24hr mode (EU time)
 - **IMODE**1 until Press again the month flashes:

the date flashes:

Press [MODE] again until tr press [ADJ] to adjust the month.
 Press [MODE] again until press [ADJ] to adjust the date.
 Press [MODE] to confirm.

- ALARM CLOCK SETTING Press [MODE] to display the alarm clock time, then press and hold [MODE] for 3 seconds until the minute starts flashing; press [ADJ] to adjust the
- minute.

 Press [MODE] the
 - Press **[MODE]** again until press **[ADJ]** to adjust the hour. Press **[MODE]** twice to confirm.

- ALARM CLOCK ON/OFF
- Press [MODE] to enter the alarm clock state. Press [ADJ] and the alarm clock symbol @ will
 - appear • Press [ADJ] and the announce hour symbol •))) will appea
- When the announce hour symbol is switched on the HUDY Personal Racing Display will announce the hour by a double beep. Press [ADJ] once again, and the alarm clock and
- Press | AUJ| once again, and the alarm clock and announce hour symbols will appear together (meaning that the alarm clock and announce hour function are both turned on simultaneously). (2) (*)
 Press [MODE] to confirm ON.
 Continue to press [ADJ] to toggle the alarm clock of the same clock of the s
 - off.

Press [MODE] to confirm OFF.

CALENDAR DISPLAY With the clock mode active, press **[ADJ]** to display the date. It will automatically revert back after 3

seconds

- MAX/MIN HUMIDITY AND TEMPERATURE DISPLAY Press [MEMO] to display MAX/MIN humidity and
 - temperature from memory.

 Press and hold [MEMO] for 2 seconds to clear the memory.

- ENVIRONMENT COMFORT DISPLAY T] indicator appears when the 20-26°C (68-78.8°F) and relative The [COMFORT] is
- temperature humidity is ! 50-70% RH. temperature
- The [WET] indicator appears at any tempe when relative humidity is higher than 70% RH.
 The [DRY] indicator appears at any tempe when relative humidity is below 50% RH. temperature

BATTERY

The display unit uses a AAA 1.5v dry cell battery. When the battery is drained, dispose of properly.

