

RACE	BASIC SET-UP	
TRACK	CARPET	
NAME	XRAY FACTORY	DATE

LAPS		BEST LAP TIME	sec
QUALIFYING POSITION		FINAL POSITION	

TRACK			
SIZE	<input type="checkbox"/> OPEN	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> TIGHT
TRACTION			
SURFACE	<input type="checkbox"/> SMOOTH	<input type="checkbox"/> MEDIUM	<input type="checkbox"/> BUMPY
TYPE	<input type="checkbox"/> CLAY	<input type="checkbox"/> CARPET	<input type="checkbox"/> ASTRO
CONDITION	<input type="checkbox"/> BLUE GROOVE	<input type="checkbox"/> HARD PACKED	<input type="checkbox"/> DRY
	<input type="checkbox"/> DUSTY	<input type="checkbox"/> LOAMY	<input type="checkbox"/> WET

DIFFERENTIAL TYPE		
FRONT ↓	MIDDLE ↓	REAR ↓
GEAR DIFF <input checked="" type="checkbox"/>	GEAR DIFF <input type="checkbox"/>	GEAR DIFF <input checked="" type="checkbox"/>
BALL DIFF <input type="checkbox"/>	SLIPPER <input checked="" type="checkbox"/>	BALL DIFF <input type="checkbox"/>
ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>	ACTIVE DIFF <input type="checkbox"/>
60° 90° 120°	60° 90° 120°	60° 90° 120°
OIL 10K cst	OIL cst	OIL 10K cst

SATELLITE GEARS		
COMPOSITE <input checked="" type="checkbox"/>	COMPOSITE <input type="checkbox"/>	COMPOSITE <input checked="" type="checkbox"/>
STEEL <input type="checkbox"/>	STEEL <input type="checkbox"/>	STEEL <input type="checkbox"/>
40T <input checked="" type="checkbox"/>	41T	CROWN GEAR 40T <input checked="" type="checkbox"/>
		41T

CENTRAL SLIPPER & ONE-WAY SETTING	
	ONE-WAY TIGHTNESS
SLIPPING ADJUSTMENT	LOOSE
13 mm	1 CW TURN (BASIC SETUP)
	FULLY TIGHTEN

GEARING	
PINION	81
	CENTER DIFF SPUR

FRONT	SHOCKS	REAR
42mm - 4 DOTS	SPRINGS	57mm - 3 DOTS
cst 700	OIL	cst 550
% 0	REBOUND	% 0
<input checked="" type="checkbox"/> 2 HOLES	PISTONS	<input checked="" type="checkbox"/> 2 HOLES
<input type="checkbox"/> 3 HOLES	<input type="checkbox"/> ø1.2mm <input type="checkbox"/> ø1.3mm <input checked="" type="checkbox"/> ø1.6mm <input type="checkbox"/> ø1.7mm	<input type="checkbox"/> 3 HOLES
<input type="checkbox"/> 6 HOLES	CUSTOM PISTONS	<input type="checkbox"/> 6 HOLES
	mm mm	

FRONT	ANTI ROLL BAR	REAR
1.8	THICKNESS	1.8
mm		mm

FRONT	TIRES	REAR
	BRAND	
	COMPOUND	
	INSERTS	
XRAY	WHEELS	XRAY

ELECTRONICS	
MOTOR	SPEEDO
MOTOR TIMING	BATTERY
BATTERY SIZE	
<input type="checkbox"/> STD. SHORT	<input type="checkbox"/> LOW SHORT

BODY	
TYPE	XRAY GAMMA 4C
	STANDARD <input checked="" type="checkbox"/> LIGHT

COMMENTS	

