

T-Maxx (Model 49077-3) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

	Air Filters
262	Air filter and pre-filter inserts, foam (high-volume) (3) (pre-oiled,
67	assembled) (TRX 2.5, 2.5R, 3.3) Air filter body (high-volume)/ filter support/ cap/ foam filter, pre-filter/
.07	T-Maxx® filter base (angled)/ wire mount/ hardware (1 each) (Fits
	Maxx® trucks) (TRX® 2.5, 2.5R, 3.3)
63	Oil, air filter
	Bearings & Bushings
11	Ball bearings (5x11x4mm) (2)
28	Ball bearings (5x8x2.5mm) (2)
19	Ball bearings, blue rubber sealed (10x15x4mm) (2)
16 14	Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (5x8x2.5mm) (2)
17	Ball bearings, blue rubber sealed (5x6x2.5mm) (2)
80	Ball bearings, blue rubber sealed (6x13x5mm) (2)
18	Ball bearings, blue rubber sealed (8x16x5mm) (2)
45	Bellcrank bushings (plastic) (5x8x2.5mm) (4)
	Body & Accessories
26	Antenna caps, vinyl (2)/ antenna spool
26	Antenna crimp nut, aluminum (blue-anodized)/ antenna nut tools
26R	Antenna crimp nut, aluminum (red-anodized)/ antenna nut tools
26 70X	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Battery holder, 4-cell/ on-off switch
35	Body clip (mounting clip), angled, 90-degrees (10)
35A	Body clip (mounting clip), angled, 90 degrees (black) (10)
34	Body clips (12) (standard size)
34	Body clips, heavy duty (12)
14R	Body mount posts, front (2)/ body mount, rear/ body mount screw pins (4)
15	Body washers (8)
15	Body washers, foam adhesive (10)
21	Body, T-Maxx® (long wheelbase) (clear, requires painting)/
	window, lights decal sheet
21X	Body, T-Maxx®, ProGraphix® (long wheelbase) (replacement for painted body. Graphics are painted, requires paint and final
	color application)/ window, grille, lights decal sheet
14	Decal sheet, racing sponsors
20X	Decal sheets, T-Maxx® 3.3 (long wheelbase) (model 4908)
50	Official Team Traxxas® racing decal set (flag logo/ 6-color)
8 5 74	Tires, rubber (2) (fits Traxxas® wheelie bar wheels)
74 77	Wheelie bar arm (1)/ connector (1)/ 3x12 SS (hex drive) (4) Wheelie bar mount (1)
75	Wheelie bar, assembled (fits all T-Maxx® and E-Maxx® trucks)
' 6	Wheels (4)/ axles (2), for Maxx® wheelie bar
36A	Wheels, aluminum (blue-anodized) (2)/ 5x8mm ball bearings (4)/
	axles (2)/ rubber tires (2)
86	Wheels, aluminum (red-anodized) (2)/ 5x8mm ball bearings (4)/ axles (2)/ rubber tires (2)
66	Brake Components
6 7	Brake adapter, hex aluminum (blue) Brake cam (blue)/ cam lever/ 3mm set screw
57 54	Brake disc (40mm steel)
4X	Brake disc (high performance, vented)
65	Brake pad set (inner and outer calipers with bonded friction material)
78	Screws, 3x21mm button-head machine (hex drive) (partially threaded,
	Revo brake bolts) (6)
	Bumpers & Skidplates
30	Bulkhead cross braces (2)/ 3x25mm CS screws (8)
36	Bumper mounts, front (l&r)/ bumper mounts, rear (l&r)/ 3x12mm RHM screws (8)
5X	Bumpers, 6061-T6, brushed aluminum (f&r)
35	Bumpers, satin finished (f&r)
9	Screws, 3x15mm button-head machine (hex drive) (6)
37	Skidplate, front plastic/ stainless steel plate (black)
37A	Skidplate, front plastic (grey)/ stainless steel plate
38	Skidplate, rear plastic/ stainless steel plate (black)
38A 69	Skidplate, rear plastic (grey)/ stainless steel plate Skidplate, transmission, nylon (grey) (for long wheelbase chassis)
85	Tires, rubber (2) (fits Traxxas® wheelie bar wheels)
74	Wheelie bar arm (1)/ connector (1)/ 3x12 SS (hex drive) (4)
	Wheelie bar mount (1)
77	
7 5	Wheels (4)/ axles (2), for Maxx® wheelie bar

anangeu a	ipitabetically.
5186A	Wheels, aluminum (blue-anodized) (2)/ 5x8mm ball bearings (4)/ axles (2)/ rubber tires (2)
5186	Wheels, aluminum (red-anodized) (2)/ 5x8mm ball bearings (4)/ axles (2)/ rubber tires (2)
	Chassis & Attachments
170V	
3170X 1925X	Battery holder, 4-cell/ on-off switch Box, battery (grey)/ adhesive foam chassis pad/charge jack plug (rubber)
5159	Box, receiver (upper and lower halves)/ clip (1)/ foam pad
1963	Chassis braces, lower (black) (for long wheelbase chassis) (2)
5122X	Chassis, T-Maxx®, long wheelbase (extended 30mm) (6061-T6
	aluminum, 4.0mm) (blue anodized)
5167	Slide carb linkage bellcrank post/ 5x8x2.5 plastic bushing (2)/ bellcrank/ 5x8x0.5 fiber washer (2)/ 3x10 WM
5185	Tires, rubber (2) (fits Traxxas® wheelie bar wheels)
1974	Wheelie bar arm (1)/ connector (1)/ 3x12 SS (hex drive) (4)
1977	Wheelie bar mount (1)
1975	Wheelie bar, assembled (fits all T-Maxx® and E-Maxx® trucks)
1976	Wheels (4)/ axles (2), for Maxx® wheelie bar
5186A	Wheels, aluminum (blue-anodized) (2)/ 5x8mm ball bearings (4)/ axles (2)/ rubber tires (2)
5186	Wheels, aluminum (red-anodized) (2)/ 5x8mm ball bearings (4)/ axles (2)/ rubber tires (2)
	Clutch & Related Parts
611	Ball bearings (5x11x4mm) (2)
120	Clutch bell, (20-tooth)/ 5x8x0.5mm fiber washer (2)/ 5mm E-clip (requires #4611-ball bearings, 5x11x4mm (2)
122	Clutch bell, (22-tooth)/ 5x8x0.5mm fiber washer (2)/ 5mm E-clip (requires #4611-ball bearings, 5x11x4mm (2))
124	Clutch bell, (24-tooth)/ 5x8x0.5mm fiber washer (2)/ 5mm E-clip (requires #4611-ball bearings, 5x11x4mm (2))
146X	Clutch shoes (2)/ spring (T-Maxx®/Revo®/Jato®/Nitro 4-Tec®)
3281	Cone, split beveled
1633	E-clips/ C-rings
6542X	Flywheel (large, knurled for use with starter boxes)
5244	Flywheel nut (TRX® 2.5, 2.5R, 3.3)
3542	Flywheel with magnet (35mm)
1985	PTFE-coated washers, 5x8x0.5mm (20) (use with ball bearings)
	Differential Components
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
5117	Ball bearings, blue rubber sealed (6x12x4mm) (2)
5118	Ball bearings, blue rubber sealed (8x16x5mm) (2)
5381	Carrier, differential/ x-ring gaskets (2)/ ring gear gasket/ 6x10x0.5 TW
5136X	Differential oil kit (1 each: 10K, 30K, 50K weights)
5382X	Gear set, differential (output gears (2)/ spider gears (2)/ spider gear shaft/ diff carrier support)
3979	Housings, differential (left & right)/ pinion collar (1)
5130	Oil, differential (100K weight) (.7 oz (20cc))
5135	Oil, differential (10K weight)
5136	Oil, differential (30K weight)
5039	Oil, differential (500K weight)
5137	Oil, differential (50K weight)
5379X	Ring gear, differential/ pinion gear, differential
5379R	Ring gear, differential/ pinion gear, differential (machined, spiral
005	cut) (front)
3965	Screws, 2.5x8mm cap-head machine (6)
	Driveline Components
5334	Axle carriers, left & right (1 each)
5334R	Axle carriers, left & right (1 each) (use with larger 6x13mm ball bearings)/ bearing adapters (for 6x12mm ball bearings) (2)/ dust
	boot retainers (4)
5459	Boots, driveshaft (rubber) (2)
5153	Drive cups, inner (2) Revo®/Maxx® (steel constant-velocity driveshafts)/screw pin, M4/15 (2)
5451X	Driveshaft assembly (1), left or right (fully assembled, ready to install)/
5154	4x15mm screw pin (1) Driveshaft, steel constant-velocity, Revo®/Maxx® (shaft only, 128.5mm)/ drive cup pin (1)
5451R	Driveshafts, Revo®/Maxx® (steel constant-velocity) (assembled w/inner & outer dust boots) (for models w/sealed pivot ball
5150	suspension & 3.8" wheels) (4) E-clips, 1.5mm (24)
5456	Half shafts, center front (Revo 3.3) (internal splined (1)/ external
	splined (1)/ external splined (1)/ external splined (1)/ external splined (1)/ (1)) (plastic parts only)

Page 2 T-Maxx: TRX 3.3, TQi 2.4GHz Radio System, Traxxas Link Wireless Module, & TSM (Model 49077-3) Parts List

Page 2	T-Maxx: TRX 3.3, TQi 2.4GHz Radio System, Traxxa
4955	Pins, axle (2.5x12mm) (4)
5129	Rebuild kit (for Revo®/Maxx® steel constant-velocity
	driveshafts) (includes pins, dustboots, & lube for 2 driveshafts
	assemblies)
5145	Screw pin, 4x15mm (6)
5189	Screw pins, 4x13mm (with threadlock) (4)
5454	Stub axle (steel) (2)
5166	Stub axle, (1)/ axle sleeve (1) Revo®/Maxx® (steel constant- velocity driveshaft)
5452	U-joints, driveshaft (carrier (4)/ 4.5mm cross pin (4)/ 3mm cross pin
5452	(4)/ e-clips (20)) (metal parts for 2 driveshafts)
4954	Wheel hubs, hex (2)/ axle pins (2.5x12mm) (2)
4954R	Wheel hubs, hex (steel)
4954X	Wheel hubs, hex, 6061-T6 aluminum (blue) (4)/ axle pins
	(2.5x10mm) (4)
5353X	Wheel hubs, splined, 17mm (blue-anodized) (4)/ wheel nuts, splined, 17mm (blue-anodized) (4)/ screw pins, 4x13mm (with
	threadlock) (4)
5353G	Wheel hubs, splined, 17mm (green-anodized) (4)/ wheel nuts,
	splined, 17mm (blue-anodized) (4)/ screw pins, 4x13mm (with
	threadlock) (4)
5353R	Wheel hubs, splined, 17mm (red-anodized) (4)/ wheel nuts,
	splined, 17mm (red-anodized) (4)/ screw pins, 4x13mm (with threadlock) (4)
5353	Wheel nuts, splined, 17mm (blue-anodized) (4)
5353A	Wheel nuts, splined, 17mm (green-anodized) (4)
5457	Yoke, brake (1)/ torque pins (2)/ 4x15mm screw pin
5458X	Yokes, differential and transmission (2)/ 4x15mm screw pins (2)
5453	Yokes, stub axle (2)/ pins (2)
	Engine & Servo Mounts
5160	Engine mount, aluminum/ 3x10 CS with washers (8)
4960X	Engine mount, machined 6061-T6 aluminum (blue) (w/ screws)
	(Maxx® Series)
3159	Screws, 3x10mm cap-head machine (hex drive) (6)/ lock washers (6)/
4049	hex wrench
4918 4918X	Servo mounts, steering/ shift (f&r) (black) Servo mounts, steering/ shift (machined aluminum) (blue) (f&r)/
43107	machine screws (8)
4918A	Servo mounts, steering/shift (f&r)(grey)
4919	Servo mounts, throttle/ brake (1) (black)
4919X	Servo mounts, throttle/ brake (machined aluminum) (blue) (f&r)/
	machine screws (8)
4919X 4919A	machine screws (8) Servo mounts, throttle/brake (1) (grey)
4919A	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Components
	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engine Components Cooling head, PowerTune (machined aluminum, blue-anodized)
4919A 5238R	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engine Common Stress Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5)
4919A 5238R 3232X	machine screws (8) Servo mounts, throttle/brake (1) (grey) Ingine Colling (1) (0) (1) (1) (1) Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket
4919A 5238R 3232X 5228	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Colling (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)
4919A 5238R 3232X	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Collige Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3)
4919A 5238R 3232X 5228 5290	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Colling (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)
4919A 5238R 3232X 5228 5290 5211R 4859	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engine Component Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4)
4919A 5238R 3232X 5228 5290 5211R 4859 3932	machine screws (8) Servo mounts, throttle/brake (1) (grey) Entrine Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6)
4919A 5238R 3232X 5228 5290 5211R 4859 3932 5277	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engine Composition Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch, 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3)
4919A 5238R 3232X 5228 5290 5211R 4859 3932	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engine Composition (1), (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)
4919A 5238R 3232X 5290 5211R 4859 3932 5277 5170	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Composition (1) (grey) Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3)
4919A 5238R 3232X 5228 5290 5211R 4859 3932 5277 5170 3155	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engine Components Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) External Cable ties, medium (black) (6)
4919A 5238R 3232X 5228 5290 5211R 4859 3932 5277 5170 3155 3296	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engine Components Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Cable ties, medium (black) (6) Fittings, inlet (nipple) for fuel or water cooling (2)
4919A 5238R 3232X 5228 5290 5211R 4859 3932 5277 5170 3155	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engine Complete Karl Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Scale ties, medium (black) (6) Fittings, inlet (nipple) for fuel or water cooling (2) Hanger, metal wire (for Resonator pipe in T-Maxx® with long
4919A 5238R 3232X 5228 5290 5211R 4859 3932 5277 5170 3155 3296	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Composition (1) (grey) Engline Composition (1) (grey) Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Extension (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)
4919A 5238R 3232X 5228 5290 5211R 4859 3932 5277 5170 3155 3296 4961	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Composition (1) (grey) Engline Composition (1) (grey) Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Cable ties, medium (black) (6) Fittings, inlet (nipple) for fuel or water cooling (2) Hanger, metal wire (for Resonator pipe in T-Maxx® with long wheelbase)/ telemetry sensor wire hold-down clip Header, aluminum (T-Maxx®) (for rear exhaust engines only) (TRX 2.5, 2.5R, 3.3)
4919A 5238R 3232X 5228 5290 5211R 4859 3932 5277 5170 3155 3296 4961 5140 5256	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engine Composition (1), (1), (1), (1), (1), (1), (1), (1),
4919A 5238R 3232X 5290 5211R 4859 3932 5277 5170 3155 3296 4961 5140	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Continionients Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Cable ties, medium (black) (6) Fittings, inlet (nipple) for fuel or water cooling (2) Hanger, metal wire (for Resonator pipe in T-Maxx® with long wheelbase)/ telemetry sensor wire hold-down clip Header, aluminum (T-Maxx®) (for rear exhaust engines only) (TRX 2.5, 2.5R, 3.3) O-ring, header 12.2x1mm (TRX® 2.5, 2.5R, 3.3) Pipe coupler, molded (for use with pipes 5152 (T Maxx) & 4452R)
4919A 5238R 3232X 5228 5290 5211R 4859 3932 5277 5170 3155 3296 4961 5140 5140 5256 5246	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Continionation (1) (grey) Engline Continionation (1) (grey) Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Extintings, inlet (nipple) for fuel or water cooling (2) Hanger, metal wire (for Resonator pipe in T-Maxx® with long wheelbase)/ telemetry sensor wire hold-down clip Header, aluminum (T-Maxx®) (for rear exhaust engines only) (TRX 2.5, 2.5R, 3.3) O-ring, header 12.2x1mm (TRX® 2.5, 2.5R, 3.3) Pipe coupler, molded (for use with pipes 5152 (T Maxx) & 4452R) (TRX 2.5, 2.5R, 3.3)
4919A 5238R 3232X 5290 5211R 4859 3932 5277 5170 3155 3296 4961 5140 5256 5246 2577	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Continuonents Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Ether (1) Cable ties, medium (black) (6) Fittings, inlet (nipple) for fuel or water cooling (2) Hanger, metal wire (for Resonator pipe in T-Maxx® with long wheelbase)/ telemetry sensor wire hold-down clip Header, aluminum (T-Maxx®) (for rear exhaust engines only) (TRX 2.5, 2.5R, 3.3) O-ring, header 12.2x1mm (TRX® 2.5, 2.5R, 3.3) Pipe coupler, molded (for use with pipes 5152 (T Maxx) & 4452R) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm button-head machine (hex drive) (6)
4919A 5238R 3232X 5228 5290 5211R 4859 3932 5277 5170 3155 3296 4961 5140 5140 5256 5246	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Composition (1), (1) (1) (2) (2) (2) (2) (2) (2) (2) (2) (2) (2
4919A 5238R 3232X 5290 5211R 4859 3932 5277 5170 3155 3296 4961 5140 5256 5246 2577	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Continionients Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Cable ties, medium (black) (6) Fittings, inlet (nipple) for fuel or water cooling (2) Hanger, metal wire (for Resonator pipe in T-Maxx® with long wheelbase)/ telemetry sensor wire hold-down clip Header, aluminum (T-Maxx®) (for rear exhaust engines only) (TRX 2.5, 2.5R, 3.3) O-ring, header 12.2x1mm (TRX® 2.5, 2.5R, 3.3) Pipe coupler, molded (for use with pipes 5152 (T Maxx) & 4452R) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x15mm cap-head machine (hex drive) (with split and flat washers) (6) Tuned pipe, Resonator, R.O.A.R. legal (aluminum, double-chamber)
4919A 5238R 3232X 5290 5211R 4859 3932 5277 5170 3155 3296 4961 5140 5256 5246 22577 5142	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Continionation (1) (grey) Engline Continionation (1) (grey) Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Extractionationation (1) (2) Hanger, metal wire (for Resonator pipe in T-Max® with long wheelbase)/ telemetry sensor wire hold-down clip Header, aluminum (T-Maxx®) (for rear exhaust engines only) (TRX 2.5, 2.5R, 3.3) O-ring, header 12.2x1mm (TRX® 2.5, 2.5R, 3.3) Pipe coupler, molded (for use with pipes 5152 (T Maxx) & 4452R) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x15mm cap-head machine (hex drive) (with split and flat washers) (6) Tuned pipe, Resonator, R.O.A.R. legal (aluminum, double-chamber) (fits Maxx® vehicles with TRX® Racing Engines)
4919A 5238R 3232X 5290 5211R 4859 3932 5277 5170 3155 3296 4961 5140 5256 5246 22577 5142	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Composition (1), (1) (1) (1) (1) (1) (1) (1) (1) (1) (1)
4919A 5238R 3232X 5290 5211R 4859 3932 5277 5170 3155 3296 4961 5140 5256 5246 22577 5142	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Continionation (1) (grey) Engline Continionation (1) (grey) Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Extractionationation (1) (2) Hanger, metal wire (for Resonator pipe in T-Max® with long wheelbase)/ telemetry sensor wire hold-down clip Header, aluminum (T-Maxx®) (for rear exhaust engines only) (TRX 2.5, 2.5R, 3.3) O-ring, header 12.2x1mm (TRX® 2.5, 2.5R, 3.3) Pipe coupler, molded (for use with pipes 5152 (T Maxx) & 4452R) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x15mm cap-head machine (hex drive) (with split and flat washers) (6) Tuned pipe, Resonator, R.O.A.R. legal (aluminum, double-chamber) (fits Maxx® vehicles with TRX® Racing Engines)
4919A 5238R 3232X 5228 5290 5211R 4859 3932 5277 5170 5140 5256 5246 2577 5142 5487 4579 5280	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Continuonation (1) (grey) Engline Continuonation (1) (grey) Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Cable ties, medium (black) (6) Fittings, inlet (nipple) for fuel or water cooling (2) Hanger, metal wire (for Resonator pipe in T-Max® with long wheelbase)/ telemetry sensor wire hold-down clip Header, aluminum (T-Maxx®) (for rear exhaust engines only) (TRX 2.5, 2.5R, 3.3) O-ring, header 12.2x1mm (TRX® 2.5, 2.5R, 3.3) Pipe coupler, molded (for use with pipes 5152 (T Maxx) & 4452R) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x15mm cap-head machine (hex drive) (with split and flat washers) (6) Tuned pipe, Resonator, R.O.A.R. legal (aluminum, double-chamber) (fits Maxx® vehicles with TRX® Racing Engines) EXERCISE (Connector, wiring harness (EZ-Start® and EZ-Start® 2) Control box (complete) (EZ-Start® 2)
4919A 5238R 3232X 5228 5200 5211R 4859 3932 5277 5170 3155 3296 4961 5140 5256 5246 2577 5142 5487 5487	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Continuonents Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) EthEllst Cable ties, medium (black) (6) Fittings, inlet (nipple) for fuel or water cooling (2) Hanger, metal wire (for Resonator pipe in T-Maxx® with long wheelbase)/ telemetry sensor wire hold-down clip Header, aluminum (T-Maxx®) (for rear exhaust engines only) (TRX 2.5, 2.5R, 3.3) O-ring, header 12.2x1mm (TRX® 2.5, 2.5R, 3.3) Pipe coupler, molded (for use with pipes 5152 (T Maxx) & 4452R) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x15mm cap-head machine (hex drive) (with split and flat washers) (6) Tuned pipe, Resonator, R.O.A.R. legal (aluminum, double-chamber) (fits Maxæ vehicles with TRX® Racing Engines) ELSENT 2.5 (2.5Artt® and EZ-Start® 2) Control box (complete) (EZ-Start® 2) Control box (complete) (EZ-Start® 2)
4919A 5238R 3232X 5290 5211R 4859 3932 5277 5170 3155 3296 4961 5140 5256 5246 2577 5142 5487 5487	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Complete/brake (1) (grey) Engline Complete/brake (1) (grey) Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) EthEllst Cable ties, medium (black) (6) Fittings, inlet (nipple) for fuel or water cooling (2) Hanger, metal wire (for Resonator pipe in T-Maxx® with long wheelbase)/ telemetry sensor wire hold-down clip Header, aluminum (T-Maxx®) (for rear exhaust engines only) (TRX 2.5, 2.5R, 3.3) O-ring, header 12.2x1mm (TRX® 2.5, 2.5R, 3.3) Pipe coupler, molded (for use with pipes 5152 (T Maxx) & 4452R) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x15mm cap-head machine (hex drive) (with split and flat washers) (6) Tuned pipe, Resonator, R.O.A.R. legal (aluminum, double-chamber) (fits Maxx® vehicles with TRX® Racing Engines) Ellesting Anness (EZ-Start® and EZ-Start® 2) Control box (complete) (EZ-Start® 2) Control box battery cover w/ belt clip (EZ-Start® 2) Coush-drive elements (4) (EZ-Start® 2)
4919A 5238R 3232X 5228 5200 5211R 4859 3932 5277 5170 3155 3296 4961 5140 5256 5246 2577 5142 5487 5487	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Continuonation (1) (grey) Engline Continuonation (1) (grey) Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Cable ties, medium (black) (6) Fittings, inlet (nipple) for fuel or water cooling (2) Hanger, metal wire (for Resonator pipe in T-Maxx® with long wheelbase)/ telemetry sensor wire hold-down clip Header, aluminum (T-Maxx®) (for rear exhaust engines only) (TRX 2.5, 2.5R, 3.3) O-ring, header 12.2x1mm (TRX® 2.5, 2.5R, 3.3) Pipe coupler, molded (for use with pipes 5152 (T Maxx) & 4452R) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x15mm cap-head machine (hex drive) (with split and flat washers) (6) Tuned pipe, Resonator, R.O.A.R. legal (aluminum, double-chamber) (fits Maxx® vehicles with TRX® Racing Engines) EXENT 2.5 (2.5tart® 2) Connector, wring harness (EZ-Start® and EZ-Start® 2) Control box (complete) (EZ-Start® 2) Control box battery cover w/ belt clip (EZ-Start® 2) Cush-drive elements (4) (EZ-Start® 2) EZ-Start® 2, complete system with controller, drive unit, wiring
4919A 5238R 3232X 5290 5211R 4859 3932 5277 5170 3155 3296 4961 5140 5256 5246 2577 5142 5487 5142 5487	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Continuon(1) (grey) Engline Continuon(1) (grey) Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Exhibitings, inlet (nipple) for fuel or water cooling (2) Hanger, metal wire (for Resonator pipe in T-Maxx® with long wheelbase)/ telemetry sensor wire hold-down clip Header, aluminum (T-Maxx®) (for rear exhaust engines only) (TRX 2.5, 2.5R, 3.3) O-ring, header 12.2x1mm (TRX® 2.5, 2.5R, 3.3) Pipe coupler, molded (for use with pipes 5152 (T Maxx) & 4452R) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x15mm cap-head machine (hex drive) (with split and flat washers) (6) Tuned pipe, Resonator, R.O.A.R. legal (aluminum, double-chamber) (fits Maxx® vehicles with TRX® Racing Engines) Exsert 2.8 Caster 2.9 Control box (complete) (EZ-Start® and EZ-Start® 2) Control box (complete) (EZ-Start® 2) Cush-drive elements (4) (EZ-Start® 2) Cush-drive elements (4) (EZ-Start® 2) Cush-drive elements (4) (EZ-Start® 2) Cush-drive unit, wiring harness
4919A 5238R 3232X 5290 5211R 4859 3932 5277 5170 3155 3296 4961 5140 5256 5246 2577 5142 5487 5487	machine screws (8) Servo mounts, throttle/brake (1) (grey) Engline Continuonation (1) (grey) Engline Continuonation (1) (grey) Cooling head, PowerTune (machined aluminum, blue-anodized) (TRX® 3.3), head protector (1), 3x6mm CCS (5) Glow plug, super-duty (long-medium)/gasket Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3) Piston/sleeve (matched set), wrist pin clips (2) (TRX® 3.3) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm flat-head machine (hex drive) (4) Screws, 3x6mm flat-head machine (hex drive) (6) Shaft, starter (TRX® 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3) Cable ties, medium (black) (6) Fittings, inlet (nipple) for fuel or water cooling (2) Hanger, metal wire (for Resonator pipe in T-Maxx® with long wheelbase)/ telemetry sensor wire hold-down clip Header, aluminum (T-Maxx®) (for rear exhaust engines only) (TRX 2.5, 2.5R, 3.3) O-ring, header 12.2x1mm (TRX® 2.5, 2.5R, 3.3) Pipe coupler, molded (for use with pipes 5152 (T Maxx) & 4452R) (TRX 2.5, 2.5R, 3.3) Screws, 3x10mm button-head machine (hex drive) (6) Screws, 3x15mm cap-head machine (hex drive) (with split and flat washers) (6) Tuned pipe, Resonator, R.O.A.R. legal (aluminum, double-chamber) (fits Maxx® vehicles with TRX® Racing Engines) EXENT 2.5 (2.5tart® 2) Connector, wring harness (EZ-Start® and EZ-Start® 2) Control box (complete) (EZ-Start® 2) Control box battery cover w/ belt clip (EZ-Start® 2) Cush-drive elements (4) (EZ-Start® 2) EZ-Start® 2, complete system with controller, drive unit, wiring

5275	Housing set (inner, outer)/ 3x12mmBCS (5)/ 3x20BCS (1)/ motor
4504	bushing (EZ-Start® 2)
4581 4581X	Lead wire, glow plug (blue) (EZ-Start® and EZ-Start® 2) Lead wire, glow plug (blue) (EZ-Start® and EZ-Start® 2)/ molex
	pin extractor (use where glow plug wire does not have bullet
	connector)
5279 5211R	Motor (hi-torque)/ pinion gear/ motor bushing (EZ Start 2) Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX 2.5,
52 H K	2.5R, 3.3)
5169	Screws, 2.6x8mm countersunk machine (6)
5282	Screws, 3x12mm button-head machine (6) (starter attachment screws
2578	with threadlock) Screws, 3x12mm button-head machine (hex drive) (6)
5277	Shaft, starter (TRX® 2.5, 2.5R, 3.3)
	Front Suspension & Steering
4934X	Aluminum caps, pivot ball (blue-anodized) (4)
5334R	Axle carriers, left & right (1 each) (use with larger 6x13mm ball
	bearings)/ bearing adapters (for 6x12mm ball bearings) (2)/ dust boot retainers (4)
2728	Ball bearings (5x8x2.5mm) (2)
4944	Bellcrank posts, aluminum (2)/ steering link threaded rod (3x25mm)/
2020	long rod ends (2)
3930 4930R	Bulkhead cross braces (2)/ 3x25mm CS screws (8) Bulkheads (I & r) (front) (grey)
4930X	Bulkheads, front (machined 6061-T6 aluminum) (blue) (l&r)
	(requires use of 4939X suspension pins)
5134 5355	Caster spacers (4)/ shims (4) Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer
0000	adjustment shims; 3.5mm (2), 1.17mm (2)
5378X	Pivot ball caps (4)/ dust boots, rubber (4)/ dust plugs, rubber (4)/ dust
4933	boot retainers, black (4), blue (4) (2 pkgs. req. to complete truck)
4933 4933X	Pivot balls (4)/ pivot ball cap bushings (4) Pivot balls, hard-anodized 7075-T6 aluminum (4)/ pivot ball cap
	bushings (4)
5347	Rod ends, Revo® (large) with hollow balls (12)
2742X 4859	Rod ends, short (6)/ hollow balls (6) Screws, 3x10 flathead machine (hex drive) (4)
5345R	Servo horns, steering, long (2), short (2)/ linkage, steering (3x20mm
	turnbuckle) (2)/ rod ends (short) (4)/ hollow balls (4)
2070 4917R	Servo, digital high-torque (ball bearing)
4917R 4945	Shock tower (for rectangular body posts) Steering bellcranks/ servo saver/ servo saver spring/ servo spring
1010	retainer (requires 5x11mm BB (2))
5132R	Suspension arms (lower) (2) (fits all Maxx® series)
5131R 5161	Suspension arms (upper) (2) (fits all Maxx® series) Suspension screw pin set, hardened steel (hex drive)
5141A	Toe links, Maxx® (TUBES black-anodized, 7075-T6 aluminum,
	stronger than titanium) (112mm, front) (2)/ rod ends (4)/
	aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension & 3.8' wheels)
5141R	Toe links, Maxx® (TUBES red-anodized, 7075-T6 aluminum,
	stronger than titanium) (112mm, front) (2)/ rod ends (4)/
	aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension & 3.8" wheels)
5141	Turnbuckles, toe links (5.0mm steel) (front) (2)
	Fuel Tank & Line
3147	Fuel line (1 foot)
3147X	Fuel line (610mm or 2ft)
4948 4958	Fuel Tank (125cc) Fuel tank rebuild kit (contains cap, foam washer, o-ring, upper/lower
-300	retainers, screw, spring and screw pin)
3149A	Heat shield tubing, fiberglass (2) (black)
	Fuel, Lubricants & Supplies
5001	Bottle, fuel filler (500cc)
3232X	Glow plug, super-duty (long-medium)/gasket
5148 5263	Grease, white lithium Oil, air filter
5001R	Rebuild kit, fuel filler bottle (includes bottle lid (1) and
	dispensing tube caps, rubber (2) (fits 8mm or 5/16" dispensing
5070	tube)) Top Fuel®, 20% nitro (gallon)
5020	Top Fuel®, 20% nitro (quart)
5080	Top Fuel®, 33% nitro (gallon)
5030	Top Fuel®, 33% nitro (quart)
	Hardware
5526	Antenna crimp nut, aluminum (blue-anodized)/ antenna nut tools
5526R 3935	Antenna crimp nut, aluminum (red-anodized)/ antenna nut tools Body clip (mounting clip), angled, 90-degrees (10)
3935A	Body clip (mounting clip), angled, 90-degrees (10) Body clip (mounting clip), angled, 90-degrees (black) (10)
1834	Body clips (12) (standard size)

Page 3 T-Maxx: TRX 3.3, TQi 2.4GHz Radio System, Traxxas Link Wireless Module, & TSM (Model 49077-3) Parts List

Page 3	T-Maxx: TRX 3.3, TQI 2.4GHz Radio System, Traxx	as Li
3934	Body clips, heavy duty (12)	6533
3930	Bulkhead cross braces (2)/ 3x25mm CS screws (8)	3932
5150	E-clips, 1.5mm (24)	6552
1633	E-clips/ C-rings	6526
5477 5478	Flat wrench, 5mm (blue-anodized aluminum) Flat wrench, 8mm (blue-anodized aluminum)	6520
3980	Glow plug wrench (universal wrench)	6520
2584	Head screws, 3x12mm cap-head machine (hex drive) (6) (TRX 2.5,	6521
	2.5R, 3.3)	2071
2586 5476X	Head screws, 3x15mm cap-head machine (hex drive) (6) (TRX 2.5)	2074
5355	Hex wrenches; 1.5mm, 2mm, 2.5mm, 3mm, 2.5mm ball Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer	2070 2075
0000	adjustment shims; 3.5mm (2), 1.17mm (2)	6553
5475	Multi-tool (plastic)	6550
2745	Nuts, 3mm nylon locking (12)	
4147X 5147X	Nuts, 5mm flanged nylon locking (aluminum, blue-anodized) (4) Nuts, 5mm flanged nylon locking (steel, serrated) (8)	6550 6551
4147	Nuts, 5mm nylon locking (8)	0001
3982	PTFE-coated 6x8x0.5 (10)	6507
1985	PTFE-coated washers, 5x8x0.5mm (20) (use with ball bearings)	
5347	Rod ends, Revo® (large) with hollow balls (12)	6529
2742X 3215	Rod ends, short (6)/ hollow balls (6) Screws, 2.5x6mm cap-head machine (hex drive) (6)	0523
3965	Screws, 2.5x8mm cap-head machine (6)	6530
5169	Screws, 2.6x8mm countersunk machine (6)	
2562	Screws, 2.6x8mm roundhead machine (6)	6511 3034
3161	Screws, 2x8mm countersunk machine (6)	3034
2577	Screws, 3x10mm button-head machine (hex drive) (6)	
3159	Screws, 3x10mm cap-head machine (hex drive) (6)/ lock washers (6)/ hex wrench	4907
2551	Screws, 3x10mm countersunk machine (6) (hex drive)	4907
4859	Screws, 3x10 flat-head machine (hex head) (4)	
5282	Screws, 3x12mm button-head machine (6) (starter attachment screws	
2578	with threadlock) Screws, 3x12mm button-head machine (hex drive) (6)	4934
2552	Screws, 3x12mm countersunk machine (6) (hex drive)	5334
2579	Screws, 3x15mm button-head machine (hex drive) (6)	5334
5142	Screws, 3x15mm cap-head machine (hex drive) (with split and flat	
0550	washers) (6)	4914
2553 2580	Screws, 3x15mm countersunk machine (6) (hex drive) Screws, 3x20mm button-head machine (hex drive) (6)	
4978	Screws, 3x21mm button-head machine (hex drive) (b)	3930
	threaded, Revo brake bolts) (6)	4929 4929
2554	Screws, 3x6mm cap-head machine (hex drive) (6)	4929
3932 2576	Screws, 3x6mm flat-head machine (hex drive) (6) Screws, 3x8mm button-head machine (hex drive) (6)	5134
2550	Screws, 3x8mm countersunk machine (6) (hex drive)	5355
4897	Screws, set (grub) 4mm (6) (with threadlock)	5378
2743	Set (grub) screws, 3mm hardened (12)	5576
3642X	Shoulder screws, Ultra Shocks (3x12 hex drive) (6)	4933
3981 2746	Washer, PTFE-coated 6x9.5x.5 (10) Washers, 3x6mm metal (12)	4933
2140	Manuals	5347
5299R	Engine Manual, TRX® 2.5, 2.5R, 3.3	5348
5299K		4917
4700	Radio System, Batteries & Chargers	5132
1726 6548	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1) Battery door, transmitter (replacement for #6516, 6517, 6528, 6529,	5131 5161
0010	6530 transmitters)	4956
2914	Battery, Power Cell AA Alkaline (4)	5143
3037	Battery, RX Power Pack (5-cell hump style, NiMH, 1200mAh)	
2919 2734	Battery, Series 1 Power Cell 1800mAh (NiMH, 6-C flat, 7.2V, Sub-C) Cable ties (small) (10)	
2977	Charger, DC, 2 amp (Molex) (5 - 6 cell, 6.0 - 7.2 volt, NiMH)	5143
2972	Charger, EZ-Peak® Dual, 100W, NiMH/LiPo with iD® Auto Battery	
	Identification	
2973	Charger, EZ-Peak® Live Dual, 200W, NiMH/LiPo with iD® Auto Battery Identification	5143
2971	Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery Identification	
2970	Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD® Auto Battery Identification	5277 5170
6525	Communication link, telemetry expander	
2978	Fuse, charger, 5A (2) (for #2974, 2975, 2977)	2666
2010 2072A	Gear set (for 2018 servos) Gear set (for 2070, 2075 servos)	2662
6556	Gear set (for 2070, 2075 servos) Mount, telemetry expander (fits XO-1®, E-Revo®*, Summit*, all Maxx® trucks, Revo® 3.3, Slayer Pro 4X4) (*requires rear chassis	4962
	brace #5632)	2669
6536	Mounts, RPM sensor (nitro engines)/ 3x10mm CS with split and flat washers (2)	
		2362

533	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)
3932	Screws, 3x6mm flat-head machine (hex drive) (6)
552	Seal kit, expander box (includes o-ring, seals, and silicone
	grease)
526	Sensor, auto-detectable, temperature
527	Sensor, auto-detectable, voltage
520	Sensor, RPM (long)/ 3x4mm BCS (2)/ 3x4 GS (1)
521	Sensor, temperature and voltage (long)
2071	Servo case (for 2070 servo)
2074	Servo case/gaskets (for 2056 and 2075 waterproof servos)
2070	Servo, digital high-torque (ball bearing)
2075	Servo, digital high-torque (ball bearing), waterproof
553X	Telemetry expander 2.0 and GPS module 2.0, TQi radio system
550X	Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module)
550	Telemetry expander, TQi radio system
551X	Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander)
507R	TQi 2.4 GHz High Output radio system, 4-channel with Traxxas Link™ Wireless Module, TSM (4-ch transmitter, 5-ch micro receiver)
529	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3- channel (transmitter only)
530	Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4- channel (transmitter only)
511	Traxxas Link™ Wireless Module
8034	Wiring harness for RX Power Pack, Traxxas® nitro vehicles (includes on/off switch and charge jack)
	Ready To Race Model

Ready-To-Race Model

077-3	T-Maxx® 3.3: 1/10 Scale Nitro-Powered 4WD Maxx® Monster Truck
	with TQi 2.4GHz Radio System, Traxxas Link™ Wireless Module,
	and Traxxas Stability Management (TSM)®

Rear Suspension

4934X	Aluminum caps, pivot ball (blue-anodized) (4)
5334	Axle carriers, left & right (1 each)
5334R	Axle carriers, left & right (1 each) (use with larger 6x13mm ball bearings)/ bearing adapters (for 6x12mm ball bearings) (2)/ dust boot retainers (4)
4914R	Body mount posts, front (2)/ body mount, rear/ body mount screw pins (4)
3930	Bulkhead cross braces (2)/ 3x25mm CS screws (8)
4929R	Bulkheads (I & r) (rear) (grey)
4929X	Bulkheads, rear (machined 6061-T6 aluminum) (blue)(l&r) (requires use of 4939X suspension pins)
5134	Caster spacers (4)/ shims (4)
5355	Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2)
5378X	Pivot ball caps (4)/ dust boots, rubber (4)/ dust plugs, rubber (4)/ dust boot retainers, black (4), blue (4) (2 pkgs. req. to complete truck)
4933	Pivot balls (4)/ pivot ball cap bushings (4)
4933X	Pivot balls, hard-anodized 7075-T6 aluminum (4)/ pivot ball cap bushings (4)
5347	Rod ends, Revo® (large) with hollow balls (12)
5348	Rod ends, Revo® (large, for rear toe link only) (4)
4917R	Shock tower (for rectangular body posts)
5132R	Suspension arms (lower) (2) (fits all Maxx® series)
5131R	Suspension arms (upper) (2) (fits all Maxx® series)
5161	Suspension screw pin set, hardened steel (hex drive)
4956	Tie bar, rear (1) /3x18mm BCS (2) (fits all Maxx® trucks)
5143A	Toe links, Maxx® (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension & 3.8' wheels)
5143R	Toe links, Maxx® (Tubes red-anodized, 7075-T6 aluminum, stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension & 3.8" wheels)
5143	Turnbuckles, toe links (5.0mm steel) (rear) (2)
	Recoil Starter
5277	Shaft, starter (TRX® 2.5, 2.5R, 3.3)
5170	Starter, recoil (complete with screws) (TRX 2.5, 2.5R, 3.3)
	Shocks (Pro-level Aluminum)
2666	Big Bore shock cylinder (XX-long) (1)
2662	Big Bore shocks (XX-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TiN shafts) w/o springs (rear) (2)
4962	Big Bore shocks (xx-long) (hard-anodized & PTFE-coated T6 aluminum) (assembled) w/ red springs, TiN shafts (8 pack)
2669	Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings & washers (2) (Big Bore Shocks)
2362	Rebuild kit, Ultra shocks (for 2 shocks)

Page 4 T-Maxx: TRX 3.3, TQi 2.4GHz Radio System, Traxxas Link Wireless Module, & TSM (Model 49077-3) Parts List

1942	Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws		Suspension Linkage
2742X	(2) Rod ands, short (6)/ ballow balls (6)	1633	E-clips/ C-rings
2742X 3962	Rod ends, short (6)/ hollow balls (6) Set (grub) screws, 3x25mm (8)/ 3mm nylon locknuts (8)	5355	Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer
2667	Shock caps, aluminum (Big Bore Shocks) (2)		adjustment shims; 3.5mm (2), 1.17mm (2)
2656T	Shock shafts, hardened steel, titanium nitride coated (xx-long)	5347	Rod ends, Revo® (large) with hollow balls (12)
	(2)	2742X	Rod ends, short (6)/ hollow balls (6)
2656	Shock shafts, steel, chrome finish (xx-long) (2)	3744 3642X	Servo saver w/adapters Shoulder screws, Ultra Shocks (3x12 hex drive) (6)
1765	Silicone diaphragms (4)	5161	Suspension screw pin set, hardened steel (hex drive)
1666 2668	Silicone shock oil (30 wt) Spring retainers, upper & lower (2)/ spring pre-load spacers:	5141A	Toe links, Maxx® (TUBES black-anodized, 7075-T6 aluminum,
	1mm (4)/ 1.5mm (2)/ 2mm (2)/ 4mm (2)/ 8mm (2) (Big Bore Shocks)		stronger than titanium) (112mm, front) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension & 3.8' wheels)
4649R	Springs, red (for big bore shocks) (2.5 rate) (2)	5143A	Toe links, Maxx® (TUBES black-anodized, 7075-T6 aluminum,
	Shocks (Ultra Shocks)		stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum
3766A	Body, Ultra Shock(s) (XXL) (grey) (2)		wrench (1) (For Maxx® models w/sealed pivot ball suspension &
2362	Rebuild kit, Ultra shocks (for 2 shocks)	5141R	3.8' wheels) Toe links, Maxx® (TUBES red-anodized, 7075-T6 aluminum,
2742X 3767	Rod ends, short (6)/ hollow balls (6)	31411	stronger than titanium) (112mm, front) (2)/ rod ends (4)/
3767A	Shock caps (2)/ shock bottoms (2) Shock caps, aluminum (blue-anodized) (4) (fits all Ultra Shocks)		aluminum wrench (1) (For Maxx® models w/sealed pivot ball
3767G	Shock caps, aluminum (green-anodized) (4) (fits all Ultra Shocks)		suspension & 3.8" wheels)
		5143R	Toe links, Maxx® (Tubes red-anodized, 7075-T6 aluminum,
3767P	Shock caps, aluminum (pink-anodized) (4) (fits all Ultra Shocks)		stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension &
3767X	Shock caps, aluminum (red-anodized) (4) (fits all Ultra Shocks)		3.8" wheels)
2656T	Shock shafts, hardened steel, titanium nitride coated (xx-long)	5141	Turnbuckles, toe links (5.0mm steel) (front) (2)
2656	(2) Shock shafts, steel, chrome finish (xx-long) (2)	5143	Turnbuckles, toe links (5.0mm steel) (rear) (2)
2030 3642X	Shoulder screws, Ultra Shocks (3x12 hex drive) (6)		Team Traxxas Items
1765	Silicone diaphragms (4)	2514	Decal sheet, racing sponsors
1666	Silicone shock oil (30 wt)	6160X	DVD, Maxx® Power! Full Throttle Action (sleeve)
3769	Spring pre-load spacers: 1mm (4)/ 2mm (2)/ 4mm (2)/ 8mm (2)	9950	Official Team Traxxas® racing decal set (flag logo/ 6-color)
3768	Spring retainers, upper & lower (2)/ piston head set (2-hole (2)/ 3-hole	9909	Traxxas® racing banner, red & black (3x7 feet)
4957R	(2)) Springe, progressive rate (for Ultre Sheeke only) (progressive		Throttle & Brake Linkage
495/K	Springs, progressive rate (for Ultra-Shocks only) (progressive rate) (f/r) (4)	4967	Brake cam (blue)/ cam lever/ 3mm set screw
3757R	Springs, rear (red) (2.9 rate) (2)	3182	Collars, screw (2)/ set screws, 3mm (2)
4957	Springs, red (for Ultra Shocks only) (2.5 rate) (f/r) (2)	3147X	Fuel line (610mm or 2ft)
3762	Ultra Shocks (black) (xx-long) (complete w/ spring pre-load	3180	Rod guides (2)/ 3mm nylon locknuts (2)
	spacers & springs) (rear) (2)	4182	Servo horn, throttle-brake/ shift (1)
3762A	Ultra shocks (grey) (xx-long) (complete w/ spring pre-load spacers & springs) (2)	5167	Slide carb linkage bellcrank post/ 5x8x2.5 plastic bushing (2)/ bellcrank/ 5x8x0.5 fiber washer (2)/ 3x10 WM
		5168	Slide carb linkage set (throttle link, brake link, and hardware)
	Slipper Clutch Components	4056	Spring, throttle return (2) (Jato®, T-Maxx® 2.5R, 3.3)
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)	3184	Springs: throttle/brake/shift (3)
5478	Flat wrench, 8mm (blue-anodized aluminum)		Tires & Wheels
5366 5352R	Input shaft, transmission (slipper shaft) Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum	4147X	Nuts, 5mm flanged nylon locking (aluminum, blue-anodized) (4)
000210	friction pads (3)/ spring, Revo® (1)/ spring, Maxx® (1)/ 2x9.8mm	5147X	Nuts, 5mm flanged nylon locking (steel, serrated) (8)
	pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1))	4955	Pins, axle (2.5x12mm) (4)
5352X	Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (2)/	5666	Sidewall protector, beadlock style (blue) (2)/ 2.5x8mm CS (24)
0554	2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1))		(for use with Geode wheels)
2554 5351	Screws, 3x6mm cap-head machine (hex drive) (6) Slipper pressure plate and hub (alloy)	5664	Sidewall protector, beadlock style (green) (2)/ 2.5x8mm CS (24) (for use with Geode wheels)
0001		5667	Sidewall protector, beadlock style (red) (2)/ 2.5x8mm CS (24) (for
	Spur Gears		use with Geode wheels)
3956 2057	Spur gear, 54-tooth (0.8 metric pitch, compatible with 32-pitch)	5665	Sidewall protector, beadlock style (yellow) (2)/ 2.5x8mm CS (24)
3957 3958	Spur gear, 56-tooth (0.8 metric pitch, compatible with 32-pitch) Spur gear, 58-tooth (0.8 metric pitch, compatible with 32-pitch)		(for use with Geode wheels)
3958 3959	Spur gear, 58-tooth (0.8 metric pitch, compatible with 32-pitch) Spur gear, 62-tooth (0.8 metric pitch, compatible with 32-pitch)	5374X	Tires & wheels, assembled, glued (Gemini black chrome wheels, Talon tires, foam inserts) (2) (use with 17mm splined wheel hubs
			& nuts, part #5353X) (TSM rated)
0700	Steering Components	5374	Tires & wheels, assembled, glued (Gemini chrome wheels, Talon
2728	Ball bearings (5x8x2.5mm) (2)		tires, foam inserts) (2) (fits Maxx/Revo series)
5116 4944	Ball bearings, blue rubber sealed (5x11x4mm) (2) Bellcrank posts, aluminum (2)/ steering link threaded rod (3x25mm)/	5674	Tires & wheels, assembled, glued (Geode chrome wheels,
-0+4	long rod ends (2)		Maxx® tires (6.3" outer diameter), foam inserts) (2) (use with
2072A	Gear set (for 2070, 2075 servos)		17mm splined wheel hubs & nuts, part #5353X & beadlock-style sidewall protectors, part #5665, 5666, 5667)
5347	Rod ends, Revo® (large) with hollow balls (12)	5672	Tires & wheels, assembled, glued (Geode chrome wheels,
2579	Screws, 3x15mm button-head machine (hex drive) (6)		paddle tires, foam inserts) (2) (use with 17mm splined wheel
5345X	Servo horns, steering and throttle (for non-Traxxas® servos		hubs & nuts, part # 5353X) (TSM rated)
E24ED	(Hitec, JR, KO, Airtronics))	4973R	Tires & wheels, assembled, glued (Hurricane chrome wheels, Maxx®
5345R	Servo horns, steering, long (2), short (2)/ linkage, steering (3x20mm turnbuckle) (2)/ rod ends (short) (4)/ hollow balls (4)		tires (6.3" outer diameter), foam inserts) (2) (fits Revo®/Maxx® series)
4918	Servo mounts, steering/ shift (f&r) (black)	5174A	Tires & wheels, assembled, glued (Split-Spoke satin-finish
4918X	Servo mounts, steering/ shift (machined aluminum) (blue) (f&r)/		wheels, Talon tires, foam inserts) (2) (fits Maxx® w/sealed pivot
	machine screws (8)		ball suspension & Revo®)
4918A	Servo mounts, steering/shift (f&r)(grey)	4983A	Tires & wheels, assembled, glued (SS (Split Spoke) black
2070 2075	Servo, digital high-torque (ball bearing)		chrome wheels, Maxx® tires (6.3" outer diameter), foam inserts) (2) (fits Maxx®/Revo® series) (TSM rated)
2075 4945	Servo, digital high-torque (ball bearing), waterproof Steering bellcranks/ servo saver/ servo saver spring/ servo spring	5173	Tires & wheels, assembled, glued (SS (Split Spoke) chrome
-0-	retainer (requires 5x11mm BB (2))	-	wheels, Maxx® Chevron tires, foam inserts) (2) (fits
2537	Threaded rods (20/25/44mm 1 ea.)/ (1) 12mm set screw		Maxx®/Revo® series)
		5174	Tires & wheels, assembled, glued (SS (Split Spoke) chrome
			wheels, Talon tires, foam inserts) (2) (fits Maxx®/Revo® series)

Page 5 T-Maxx: TRX 3.3, TQi 2.4GHz Radio System, Traxxas Link Wireless Module, & TSM (Model 49077-3) Parts List

Page 5	T-Maxx: TRX 3.3, TQi 2.4GHz Radio System, Traxxa
5174R	Tires & wheels, assembled, glued (SS (Split Spoke) chrome wheels, Talon tires, foam inserts) (2) (use w/17mm splined wheel
5375R	hubs & nuts, part #5353X) Tires & wheels, assembled, glued (white dished 3.8" wheels, Response Pro tires, foam inserts) (2) (use with 17mm splined
	wheel hubs and wheel nuts, part #5353X)
5670	Tires, Canyon AT 3.8" (2)/ foam inserts (2)
4973	Tires, Maxx® 3.8" (6.3" outer diameter (160mm)) (2) (fits Revo®/Maxx® series)
5171 5375	Tires, Maxx® Chevron 3.8" (2) (fits Revo®/Maxx® series) Tires, Response Pro 3.8" (soft-compound, narrow profile, short
0010	knobby design)/ foam inserts (2)
5471	Tires, Response racing 3.8" (soft-compound, narrow profile, short knobby design)/ foam inserts (2)
5470	Tires, SportTraxx racing 3.8" (soft compound, directional and asymmetrical tread design)/ foam inserts (2)
5370	Tires, Talon 3.8" (2)/ foam inserts (2)
4954 4954R	Wheel hubs, hex (2)/ axle pins (2.5x12mm) (2) Wheel hubs, hex (steel)
4954X	Wheel hubs, hex, 6061-T6 aluminum (blue) (4)/ axle pins
5353X	(2.5x10mm) (4) Wheel hubs, splined, 17mm (blue-anodized) (4)/ wheel nuts,
	splined, 17mm (blue-anodized) (4)/ screw pins, 4x13mm (with threadlock) (4)
5353G	Wheel hubs, splined, 17mm (green-anodized) (4)/ wheel nuts, splined, 17mm (blue-anodized) (4)/ screw pins, 4x13mm (with threadlock) (4)
5353R	Wheel hubs, splined, 17mm (red-anodized) (4)/ wheel nuts, splined, 17mm (red-anodized) (4)/ screw pins, 4x13mm (with threadlock) (4)
5353	Wheel nuts, splined, 17mm (blue-anodized) (4)
5353A	Wheel nuts, splined, 17mm (green-anodized) (4)
5480X	Wheel wrench, splined, 17mm
5371	Wheels, dished 3.8" (white) (2) (use with 17mm splined wheel hubs and wheel nuts, part #5353X)
5372A	Wheels, Gemini 3.8" (black chrome) (2)
5372X	Wheels, Gemini 3.8" (black chrome) (2) (use with 17mm splined wheel hubs & nuts, part #5353X)
5372	Wheels, Gemini 3.8" (chrome) (2)
5671	Wheels, Geode 3.8" (chrome) (2) (use with 17mm splined wheel hubs & nuts, part #5353X & beadlock-style sidewall protectors, part #5665, 5666, 5667)
5373	Wheels, Hurricane 3.8" (chrome) (2)
5172A	Wheels, SS (split spoke) 3.8" (black chrome) (2) (use with 17mm splined wheel hubs & nuts, part #5353X) (fits Revo®/Maxx® series)
5172X	Wheels, SS (split spoke) 3.8" (chrome) (2) (fits Revo®/Maxx® series)
5172R	Wheels, SS (split spoke) 3.8" (chrome) (2) (use with 17mm splined wheel hubs & nuts, part #5353X) (fits Revo®/Maxx® series)
5172	Wheels, SS (split spoke) 3.8" (satin) (2) (fits Revo®/Maxx® series)
	Transmission Components
4611	Ball bearings (5x11x4mm) (2)
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
5117 5394X	Ball bearings, blue rubber sealed (6x12x4mm) (2) Forward only conversion kit (eliminates reverse)
5394 5394	Forward only shaft, steel (Revo®)
5383	Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware)
5385	Gears, hardware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware)
5384	Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware)
5386	Gear, 1st speed, 43T
5181	Gearbox halves (front & rear)/ rubber access plug/ shift detent ball/ spring/ 4mm GS/ shift shaft seal, glued
5366	Input shaft, transmission (slipper shaft)
5390	Primary clutch assembly/ 2x9.8mm pin/ 6x8x0.5 TW (1)
5393	Primary shaft/ 1st speed hub/ one-way bearing/ snap ring/ 5x8mm TW
5352R	Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum friction pads (3)/ spring, Revo® (1)/ spring, Maxx® (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1))
5352X	Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (2)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1))
4995X	Reverse installation kit (includes all components to add mechanical reverse (no Optidrive) to T-Maxx® 3.3) (includes 2060 sub-micro servo)
1647 3981	Silicone grease Washer, PTFE-coated 6x9.5x.5 (10)
	,

	Traxxas Tools
3433X	Body reamer (aluminum handle)
3433	Body reamer (plastic handle)
3436	Cap, body reamer
3432	Scissors, curved tip
3431	Scissors, straight tip
8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes
	premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm,
8722	and 8.0mm), 1/4" drive Speed bit handle, premium (rubber overmold)
8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm, 2.5mm, 3.0mm), 1/4" drive
8719	Speed Bit Master Set, nut driver, 6-piece, includes premium handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" drive
8716X	Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm, 3.0mm), 1/4" drive
8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm, 2.5mm), 1/4" drive
8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive
3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips, #0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/
	driver handle
	Turnbuckles & Threaded Rods
4944	Bellcrank posts, aluminum (2)/ steering link threaded rod (3x25mm)/
	long rod ends (2)
5355	Hollow ball, tall centered (2)/ tall offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2)
5347	Rod ends, Revo® (large) with hollow balls (12)
2742X	Rod ends, short (6)/ hollow balls (6)
5141A	Toe links, Maxx® (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (112mm, front) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball
5143A	suspension & 3.8' wheels) Toe links, Maxx® (TUBES black-anodized, 7075-T6 aluminum, stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum
	wrench (1) (For Maxx® models w/sealed pivot ball suspension & 3.8' wheels)
5141R	Toe links, Maxx® (TUBES red-anodized, 7075-T6 aluminum,
	stronger than titanium) (112mm, front) (2)/ rod ends (4)/ aluminum wrench (1) (For Maxx® models w/sealed pivot ball suspension & 3.8" wheels)
5143R	Toe links, Maxx® (Tubes red-anodized, 7075-T6 aluminum,
	stronger than titanium) (124mm, rear) (2)/ rod ends (4)/ aluminum
	wrench (1) (For Maxx® models w/sealed pivot ball suspension &
	3.8" wheels)
5141	Turnbuckles, toe links (5.0mm steel) (front) (2)
5143	Turnbuckles, toe links (5.0mm steel) (rear) (2)
	Two-Speed Components
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
5117	Ball bearings, blue rubber sealed (6x12x4mm) (2)
5394X	Forward only conversion kit (eliminates reverse)
5383	Gear set, 2-speed close ratio (2nd speed gear 40T, 13T-16T input gears, hardware)
5385	gears, naroware) Gear set, 2-speed standard ratio (2nd speed gear 39T, 13T-17T input gears, hardware)
5384	Gear set, 2-speed wide ratio (2nd speed gear 38T, 13T-18T input gears, hardware)
5386	Gear, 1st speed, 43T
5390	Primary clutch assembly/ 2x9.8mm pin/ 6x8x0.5 TW (1)
5393	Primary shaft/ 1st speed hub/ one-way bearing/ snap ring/ 5x8mm TW

If you have questions or need technical assistance, call Traxxas at:

1-888-TRAXXAS

(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com TRAXXAS.COM