

Unlimited Desert Racer (Model 85076-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

05.45	Axle Components	8430X	Tube chassis, side section (left & right) (satin black chrome- plated)
8540 8540X	Axle housing, rear/ axle supports, left & right/ axle hub, rear (2) Axle housing, rear/ differential carrier (satin black chrome-		Differential Components
554UX	plated) (internal components sold separately)	8581	Carrier, differential (front or center)/ x-ring gaskets (2)/ ring gear
3539	Axle shaft, rear		gasket/ 14.5x20 TW (2)
	Bearings & Bushings	8581X	Carrier, differential, aluminum (front or center)/ x-ring gaskets
5106A	Ball bearing, black rubber sealed (15x24x5mm) (2)	8541	(2), ring gear gasket/ 14.5x20 TW (2) Carrier, differential, rear axle (left & right halves)
5102A	Ball bearings, black rubber sealed (15x21x4mm) (2)	5136X	Differential oil kit (1 each: 10K, 30K, 50K weights)
5114A	Ball bearings, black rubber sealed (5x8x2.5mm) (2)	8576	Differential, rear (fully assembled)
5180A	Ball bearings, black rubber sealed (6x13x5mm) (2)	8583	Gear set, center differential (output gears (2)/ spider gears (4))
7019R 7020	Ball bearings, blue rubber sealed (4x8x3mm) (8) Ball bearings, blue rubber sealed (8x12x3.5mm) (2)	8582	Gear set, differential (front) (output gears (2)/ spider gears (4))
7020 5118	Ball bearings, blue rubber sealed (8x16x5.51111) (2)	8577	Gear set, rear differential (output gears (2)/ spider gears (4)) (#8581 required to build complete differential)
0110	Body & Accessories	8580	Housing, differential (front)
0544	_	8592	Housing, planetary gears (front & rear halves)
8511	Body, Desert Racer® (clear, trimmed, requires painting)/ decal sheet	5042	Oil, differential (1M weight) (standard)
8513	Body, Desert Racer®, Fox® Edition (painted)/ decals	8588	Planetary gears (4)
8514	Body, Desert Racer®, Rigid® Edition (painted)/ decals	8578	Ring gear, differential/pinion gear, differential (front)
8515	Decals, Unlimited Desert Racer®, Fox® Edition	8579 9595	Ring gear, differential/ pinion gear, differential (rear)
8516	Decals, Unlimited Desert Racer®, Rigid® Edition	8585 8584	Ring gear, planetary Spider gear shaft (2)/ spider bushing (4)
8518	Driver helmet, grey (2)	8586	Sun gear, planetary (center)
8512 8517	Interior, clear (unpainted) Window nets (2)/ 2.5x8mm CS (8)	8587	Sun gear, planetary (rear)
0317			Driveline Components
	Brake Components	8551	Drive cup (1)/ 2.5x10 CS (use only with #8550 driveshaft)
8567	Brake calipers, front or rear (grey) (4)	8555	Driveshaft, center rear, 6061-T6 aluminum (black-anodized) (fully
8569 8568	Wheel hubs, hex (disc brake rotors) (4) Wheel hubs, hex, steel (4)		assembled)/ 3mm screw pin (2)
0300		8556X	Driveshaft, center, front (steel)/ 2.5x12 screw pin
	Bumpers & Skidplates	8550	Driveshaft, steel constant-velocity (shaft only, 96mm) (1)
8535	Bumper, front/ bumper support	8556	Driveshafts, center front/ 4mm screw pin (1)/ 3x10 CS (1)
8535X 8536	Bumper, front/ bumper support (satin black chrome-plated) Bumper, rear/ bumper extension	8554	Rebuild kit, steel constant velocity driveshaft (includes drive pin & cross pin for two driveshaft assemblies)
8536X	Bumper, rear/ bumper extension (satin black chrome-plated)	8557	Screw pin, 3x11mm (with threadlock) (6)
8537X	Skidplate, front (plastic) (satin black chrome-plated)	8553	Stub axle, steel (use with #8550 driveshaft)
8537	Skidplate, front (plastic)/ support plate (steel)	8569	Wheel hubs, hex (disc brake rotors) (4)
	Chassis & Attachments	8568	Wheel hubs, hex, steel (4)
8525	Battery connector retainer/ wall support/ front & rear clips		Front Suspension & Steering
8524	Battery door/ battery strap/ retainers (2)/ latch	8552	Axle carriers, left & right (1 each)
8536	Bumper, rear/ bumper extension	8523	Bulkhead tie bar, front (steel)
8536X	Bumper, rear/ bumper extension (satin black chrome-plated)	8530	Bulkhead, front
8522	Chassis	8550 8596	Driveshaft, steel constant-velocity (shaft only, 96mm) (1) Linkage, sway bar, front (2) (assembled with hollow balls)/ sway bar
8420 8518	Chassis tray/ driveshaft clamps/ fuel filler (black) Driver helmet, grey (2)	0390	arm (left & right)
8512	Interior, clear (unpainted)	8534	Mounts, suspension arm, upper (front) (left & right)
8560	Motor mount/ pin (2)	8534X	Mounts, suspension arm, upper (front) (left & right) (satin black
8520	Nerf bars (left or right) (2)	0=40	chrome-plated)
8519	Number plates, left & right	8543	Steering bellcranks/ servo saver/ servo saver spring/ servo spring retainer/servo horn, steering
8526	Servo mount, steering	8553	Stub axle, steel (use with #8550 driveshaft)
8538	Shock mounts, rear (left & right)	8533	Suspension arm, lower left/ arm insert (assembled with hollow ball)
8538X 8521	Shock mounts, rear (left & right) (satin black chrome-plated) Skidplate, chassis	8533X	Suspension arm, lower left/ arm insert (satin black chrome-
8544	Trailing arm (2) (assembled with hollow balls)		plated) (assembled with hollow ball)
8544X	Trailing arm, aluminum (blue-anodized) (2) (assembled with	8532	Suspension arm, lower right/ arm insert (assembled with hollow ball)
	hollow balls)	8532X	Suspension arm, lower right/ arm insert (satin black chrome- plated) (assembled with hollow ball)
8544A	Trailing arm, aluminum (dark titanium anodized) (2) (assembled	8531	Suspension arms, upper (left & right) (assembled with hollow balls)
0E44D	with hollow balls)	8531X	Suspension arms, upper (left & right) (satin black chrome-plated
8544R	Trailing arm, aluminum (red-anodized) (2) (assembled with hollow balls)		(assembled with hollow balls)
8431	Tube chassis, center section, front	8546	Suspension pin retainers (upper (2), lower (1))
8431X	Tube chassis, center section, front (satin black chrome-plated)	8545	Suspension pin set (front) (3x51mm (2), 3x54mm (2), 3x93mm (2))
8432	Tube chassis, center section, rear	8596X 8598	Sway bar arms, front (satin-plated) Sway bars (front & rear)
8432X	Tube chassis, center section, rear (satin black chrome-plated)	8547	Toe links, front (2) (assembled with hollow balls)
8433	Tube chassis, center support/ cage top/ rear cage support	8547X	Toe links, front, Unlimited Desert Racer® (TUBES blue-anodized
8433X	Tube chassis, center support/ cage top/ rear cage support (satin black chrome-plated)		7075-T6 aluminum, stronger than titanium) (102mm) (2)
8434	Tube chassis, inner panels (front (2)/ middle (4)/ rear (2))		(assembled with rod ends and hollow balls)/ aluminum wrench,
8434A	Tube chassis, inner panels (silver aluminum) (front (2)/ wheel	05474	7mm (1)
	well (4)/ middle (4)/ rear (2))	8547A	Toe links, front, Unlimited Desert Racer® (TUBES dark titanium anodized, 7075-T6 aluminum, stronger than titanium) (102mm)
8434X	Tube chassis, inner panels, aluminum (blue-anodized) (front (2)/		(2) (assembled with rod ends and hollow balls)/ aluminum
	wheel well (4)/ middle (4)/ rear (2))		wrench, 7mm (1)
04245	Tube change inner people cluminum (red anadicad) (for the (0))		
8434R	Tube chassis, inner panels, aluminum (red-anodized) (front (2)/ wheel well (4)/ middle (4)/ rear (2))	8547R	Toe links, front, Unlimited Desert Racer® (TUBES red-anodized,
8434R 8430	Tube chassis, inner panels, aluminum (red-anodized) (front (2)/ wheel well (4)/ middle (4)/ rear (2)) Tube chassis, side section (left & right)	8547R	Toe links, front, Unlimited Desert Racer® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (102mm) (2) (assembled with rod ends and hollow balls)/ aluminum wrench,

	Hardware	3480	Velineon® VXL-6s Brushless Power System, waterproof (includes VXL-6s ESC and 2200Kv, 75mm motor)
2586 8447A	Head screws, 3x15mm cap-head machine (hex drive) (6) (TRX 2.5) Nuts, 5mm flanged nylon locking (aluminum, black-anodized,	3485	Velineon® VXL-6s Electronic Speed Control, waterproof (brushless) (fwd/rev/brake)
8447X	serrated) (4) Nuts, 5mm flanged nylon locking (aluminum, blue-anodized,		Radio System, Batteries & Chargers
	serrated) (4)	2872X	5000mAh 11.1v 3-Cell 25C LiPo Battery
8447G	Nuts, 5mm flanged nylon locking (aluminum, green-anodized, serrated) (4)	2888X 2889X	5000mAh 14.8v 4-Cell 25C LiPo Battery
8447R	Nuts, 5mm flanged nylon locking (aluminum, red-anodized,	2842X	5000mAh 14.8v 4-Cell 25C LiPo Battery 5000mAh 7.4v 2-Cell 25C LiPo Battery
	serrated) (4)	2843X	5800mAh 7.4v 2-Cell 25C LiPo Battery
8447	Nuts, 5mm flanged nylon locking (steel, black serrated) (8)	2890X	6700mAh 14.8v 4-Cell 25C LiPo Battery
5147X 4955	Nuts, 5mm flanged nylon locking (steel, serrated) (8)	2869X	7600mAh 7.4v 2-Cell 25C LiPo Battery
8557	Pins, axle (2.5x12mm) (4) Screw pin, 3x11mm (with threadlock) (6)	2976 2938X	AC to DC converter, 40W Adapter, Traxxas® iD® LiPo battery (adapts Traxxas iD batteries
5189	Screw pins, 4x13mm (with threadlock) (4)	2930X	to separate balance ports)
3229	Screws, 2.5x10mm cap-head machine (hex drive) (6)	1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)
3236	Screws, 2.5x12mm cap-head machine (6)	2943	Battery charge indicators (green (4), blue (4), grey (4))
3215 3965	Screws, 2.5x6mm cap-head machine (hex drive) (6) Screws, 2.5x8mm cap-head machine (6)	6548	Battery door, transmitter (replacement for #6516, 6517, 6528, 6529, 6530 transmitters)
2524	Screws, 2.5x8mm countersunk machine (b)	2914	Battery, Power Cell AA Alkaline (4)
7944	Screws, 2.6x5mm button-head, self-tapping (hex drive) (6)	2991	Battery/charger completer pack (includes #2972 Dual iD®
2577	Screws, 3x10mm button-head machine (hex drive) (6)		charger (1), #2869X 7600mAh 7.4V 2-cell 25C LiPo battery (2))
2587	Screws, 3x10mm cap-head machine (6) (no washer)	2972	Charger, EZ-Peak® Dual, 100W, NiMH/LiPo with iD® Auto Battery Identification
2578 2579	Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6)	2973	Charger, EZ-Peak® Live Dual, 200W, NiMH/LiPo with iD® Auto
2579	Screws, 3x15mm button-nead machine (nex drive) (6) Screws, 3x15mm countersunk machine (6) (hex drive)	2070	Battery Identification
2583	Screws, 3x18mm button-head machine (by drive) (6)	2971	Charger, EZ-Peak® Live, 100W, NiMH/LiPo with iD® Auto Battery
2580	Screws, 3x20mm button-head machine (hex drive) (6)	2070	Identification
2581	Screws, 3x25mm button-head machine (hex drive) (6)	2970	Charger, EZ-Peak® Plus, 4 amp, NiMH/LiPo with iD® Auto Battery Identification
2582	Screws, 3x30mm button-head machine (hex drive) (6)	6525	Communication link, telemetry expander
2516 2515	Screws, 3x45mm button-head machine (hex drive) (6) Screws, 3x4mm button-head machine (hex drive) (6)	8527	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual-
2534	Screws, 3x6mm countersunk machine (6) (hex drive)		battery 25.2 ESC to run on a single 14.8V battery pack)
2576	Screws, 3x8mm button-head machine (hex drive) (6)	6512	Cover plate, Traxxas Link™ Wireless Module
2550	Screws, 3x8mm countersunk machine (6) (hex drive)	6566	Data link, telemetry expander (connects #6550X telemetry expander 2.0 to the #3485 VXL-6s or #3496 VXL-8s electronic
3931	Screws, 3x8mm flat-head machine (hex drive) (6)		speed control)
3936	Screws, 4x10mm button-head machine (hex drive) (6)	6565	Data link, telemetry expander (connects #6550X telemetry
3938 2546	Screws, 4x14mm button-head machine (hex drive) (6) Screws, 4x15mm countersunk machine (hex drive) (6)	00707	expander 2.0 to the #6590 high-voltage power amplifier)
2597	Screws, 4x22mm button-head machine (hex drive) (6)	2072X 2252	Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos)
2596	Screws, 4x25mm button-head machine (hex drive) (6)	2072R	Gear set, metal (101 2230, 2233 servos) Gear set, metal, high speed (for 2070, 2075 servos)
2533	Screws, 4x30mm countersunk machine (hex drive) (6)	2968X	LiPo cell voltage checker/balancer (includes #2938X adapter for
2595	Screws, 4x35mm button-head machine (hex drive) (6)		Traxxas® iD® batteries)
1548 8343	Set (grub) screws, 3x4mm (8)/ 4x4mm (stainless) (4) Steering bellcranks/ hardware	2968	LiPo cell voltage checker/balancer (requires #2938X adapter for
2746	Washers, 3x6mm metal (12)	6535	Traxxas® iD® batteries) Mount, temperature sensor (electric motors)/ wire tie/ thermal
	LED Lights	0000	pad
8489	2-in-1 wire harness, LED lights (high-voltage)	6533	Receiver, micro, TQi 2.4GHz with telemetry & TSM (5-channel)
6590	High-Voltage Power Amplifier	6552	Seal kit, expander box (includes o-ring, seals, and silicone
8486	LED light bar, front (high-voltage) (52 white LEDs (double row),	6526	grease) Sensor, auto-detectable, temperature
	100mm wide)	6527	Sensor, auto-detectable, temperature
8488	LED light bar, roof (curved, high-voltage) (52 white LEDs (single	6521	Sensor, temperature and voltage (long)
8485	row), 202mm wide) LED light set, complete (includes front light bar (2), rear light bar,	2254	Servo case, aluminum (blue-anodized) (middle) (for 2250 servo)
0.100	curved roof light bar, and high-voltage power amplifier)	2253	Servo case, aluminum (red-anodized) (middle) (for 2255 servo)
8487	LED lightbar, rear, red (with amber class light) (high-voltage) (24	2251	Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos)
	red LEDs, 24 amber LEDs, 100mm wide)	2075R	Servo, digital high-speed, metal gear (ball bearing), waterproof
	Motors & Electronics		
	motors & figuriants	2250	Servo, digital high-torque 330 coreless, metal gear (ball bearing),
8527	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual-		waterproof
	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual- battery 25.2 ESC to run on a single 14.8V battery pack)	2255	waterproof Servo, digital high-torque 400 brushless, metal gear (ball
3475	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual- battery 25.2 ESC to run on a single 14.8V battery pack) Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s)	2255	waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof
3475 2072	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual-battery 25.2 ESC to run on a single 14.8V battery pack) Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s) Gear set (for 2070, 2075 servos)		waterproof Servo, digital high-torque 400 brushless, metal gear (ball
3475	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual- battery 25.2 ESC to run on a single 14.8V battery pack) Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s)	2255 2075X	waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with
3475 2072 2072X 2252 2072R	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual-battery 25.2 ESC to run on a single 14.8V battery pack) Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s) Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos)	2255 2075X 6553X 6550X	waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module)
3475 2072 2072X 2252 2072R 8560	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual-battery 25.2 ESC to run on a single 14.8V battery pack) Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s) Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Motor mount/ pin (2)	2255 2075X 6553X 6550X	waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system
3475 2072 2072X 2252 2072R	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual-battery 25.2 ESC to run on a single 14.8V battery pack) Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s) Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Motor mount/ pin (2) Motor, 2200Kv 75mm, brushless (with 6.5mm gold-plated connectors	2255 2075X 6553X 6550X	waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only
3475 2072 2072X 2252 2072R 8560	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual-battery 25.2 ESC to run on a single 14.8V battery pack) Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s) Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Motor mount/ pin (2) Motor, 2200Kv 75mm, brushless (with 6.5mm gold-plated connectors & high-efficiency heatsink)	2255 2075X 6553X 6550X	waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system
3475 2072 2072X 2252 2072R 8560 3481	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dual-battery 25.2 ESC to run on a single 14.8V battery pack) Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s) Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Motor mount/ pin (2) Motor, 2200Kv 75mm, brushless (with 6.5mm gold-plated connectors	2255 2075X 6553X 6550X 6550 6551X	waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only)
3475 2072 2072X 2252 2072R 8560 3481 2254	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dualbattery 25.2 ESC to run on a single 14.8V battery pack) Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s) Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Motor mount/ pin (2) Motor, 2200Kv 75mm, brushless (with 6.5mm gold-plated connectors & high-efficiency heatsink) Servo case, aluminum (blue-anodized) (middle) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for	2255 2075X 6553X 6550X 6550 6551X	waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2- channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-
3475 2072 2072X 2252 2072R 8560 3481 2254 2253 2251	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dualbattery 25.2 ESC to run on a single 14.8V battery pack) Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s) Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Motor mount/ pin (2) Motor, 2200Kv 75mm, brushless (with 6.5mm gold-plated connectors & high-efficiency heatsink) Servo case, aluminum (blue-anodized) (middle) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos)	2255 2075X 6553X 6550X 6550 6551X 6528 6529	waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-channel (transmitter only)
3475 2072 2072X 2252 2072R 8560 3481 2254 2253 2251 2074	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dualbattery 25.2 ESC to run on a single 14.8V battery pack) Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s) Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Motor mount/ pin (2) Motor, 2200Kv 75mm, brushless (with 6.5mm gold-plated connectors & high-efficiency heatsink) Servo case, aluminum (blue-anodized) (middle) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2056 and 2075 waterproof servos)	2255 2075X 6553X 6550X 6550 6551X	waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-
3475 2072 2072X 2252 2072R 8560 3481 2254 2253 2251 2074 8526	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dualbattery 25.2 ESC to run on a single 14.8V battery pack) Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s) Gear set (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Motor mount/ pin (2) Motor, 2200Kv 75mm, brushless (with 6.5mm gold-plated connectors & high-efficiency heatsink) Servo case, aluminum (blue-anodized) (middle) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo mount, steering	2255 2075X 6553X 6550X 6550 6551X 6528 6529	waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4-
3475 2072 2072X 2252 2072R 8560 3481 2254 2253 2251 2074	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dualbattery 25.2 ESC to run on a single 14.8V battery pack) Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s) Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Motor mount/ pin (2) Motor, 2200Kv 75mm, brushless (with 6.5mm gold-plated connectors & high-efficiency heatsink) Servo case, aluminum (blue-anodized) (middle) (for 2250 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2056 and 2075 waterproof servos)	2255 2075X 6553X 6550X 6550 6551X 6528 6529 6530	waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system Telemetry expander, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4-channel (transmitter only) Traxxas Link™ Wireless Module
3475 2072 2072X 2252 2072R 8560 3481 2254 2253 2251 2074 8526 2075R 2250	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dualbattery 25.2 ESC to run on a single 14.8V battery pack) Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s) Gear set (for 2070, 2075 servos) Gear set, metal (for 250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Motor mount/ pin (2) Motor, 2200Kv 75mm, brushless (with 6.5mm gold-plated connectors & high-efficiency heatsink) Servo case, aluminum (blue-anodized) (middle) (for 2250 servo) Servo case, aluminum (red-anodized) (middle) (for 2255 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo mount, steering Servo, digital high-speed, metal gear (ball bearing), waterproof	2255 2075X 6553X 6550X 6550 6551X 6528 6529 6530 6511	waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4-channel (transmitter only) Traxxas Link™ Wireless Module
3475 2072 2072X 2252 2072R 8560 3481 2254 2253 2251 2074 8526 2075R	Connector, 25.2 volt to 14.8 volt jumper (allows a Traxxas® dualbattery 25.2 ESC to run on a single 14.8V battery pack) Cooling fan, Velineon® VXL ESC (fits VXL-6s & VXL-8s) Gear set (for 2070, 2075 servos) Gear set, metal (for 2070, 2075 servos) Gear set, metal (for 2250, 2255 servos) Gear set, metal, high speed (for 2070, 2075 servos) Motor mount/ pin (2) Motor, 2200Kv 75mm, brushless (with 6.5mm gold-plated connectors & high-efficiency heatsink) Servo case, aluminum (blue-anodized) (middle) (for 2250 servo) Servo case, aluminum (red-anodized) (middle) (for 2255 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for 2250, 2255 servos) Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo mount, steering Servo, digital high-speed, metal gear (ball bearing), waterproof	2255 2075X 6553X 6550X 6550 6551X 6528 6529 6530	waterproof Servo, digital high-torque 400 brushless, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof Telemetry expander 2.0 and GPS module 2.0, TQi radio system Telemetry expander 2.0, TQi radio system (compatible only with #6551X GPS module) Telemetry expander, TQi radio system Telemetry expander, TQi radio system Telemetry GPS module 2.0, TQi radio system (compatible only with #6550X telemetry expander) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 2-channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 3-channel (transmitter only) Transmitter, TQi Traxxas Link™ enabled, 2.4GHz high output, 4-channel (transmitter only) Traxxas Link™ Wireless Module

Page 3 Unlimited Desert Racer: TQi Traxxas Link Enabled 2.4GHz Radio & TSM (Model 85076-4) Parts List

05.40	Rear Suspension	8450	Shocks, GTR, 134mm, silver aluminum (fully assembled w/o springs (front, threaded) (2)
8540 8540X	Axle housing, rear/ axle supports, left & right/ axle hub, rear (2) Axle housing, rear/ differential carrier (satin black chrome-	8460X	Shocks, GTR, 139mm, aluminum (blue-anodized) (fully assembled w/o springs) (rear, threaded) (2)
3539	plated) (internal components sold separately) Axle shaft, rear	8460R	Shocks, GTR, 139mm, aluminum (red-anodized) (fully assemble
8555	Driveshaft, center rear, 6061-T6 aluminum (black-anodized) (fully assembled)/ 3mm screw pin (2)	8460	w/o springs) (rear, threaded) (2) Shocks, GTR, 139mm, silver aluminum (fully assembled w/o springs
8548	Limit strap, rear suspension (2)/ 3x8 flat-head screw (4)	8461X	(rear, threaded) (2) Shocks, GTR, 160mm, aluminum (blue-anodized) (fully
8597	Linkage, sway bar, rear (2) (assembled with hollow balls)/ sway bar	040170	assembled w/o springs) (rear, no threads) (2)
0500	arm (left & right)	8461R	Shocks, GTR, 160mm, aluminum (red-anodized) (fully assemble
8538 8538X	Shock mounts, rear (left & right) Shock mounts, rear (left & right) (satin black chrome-plated)	0.404	w/o springs) (rear, no threads) (2)
8590	Spool/ spacers (left & right)/ 2.5x8 CS (4)	8461	Shocks, GTR, 160mm, silver aluminum (fully assembled w/o springs (rear, no threads) (2)
8542T	Suspension link, rear (upper) (aluminum, black-anodized)	8459	Spring retainers, lower (captured) (4)/ 2.5x10 CS (4)
8542A	(10x206mm, center to center) (2) (assembled with hollow balls) Suspension link, rear (upper) (aluminum, blue-anodized)	8443	Spring, shock, 139mm (natural finish) (GTR) (progressive, 0.937 rate, orange stripe) (2)
8542R	(10x206mm, center to center) (2) (assembled with hollow balls) Suspension link, rear (upper) (aluminum, red-anodized)	8442	Spring, shock, 139mm (natural finish) (GTR) (progressive, 1.146 rate, green stripe) (2)
8542X	(10x206mm, center to center) (2) (assembled with hollow balls) Suspension link, rear (upper) (heavy duty, steel) (7x206mm,	8441	Spring, shock, 139mm (natural finish) (GTR) (progressive, 1.250 rate, blue stripe) (2)
8542	center to center) (2) (assembled with hollow balls) Suspension link, rear (upper) (steel) (4x206mm, center to center) (2)	8444A	Spring, shock, front (blue) (GTR) (progressive, 0.833 rate, white stripe) (2)
8597X	(assembled with hollow balls) Sway bar arms, rear (satin-plated)	8444	Spring, shock, front (natural finish) (GTR) (progressive, 0.833 rate, white stripe) (2)
8598	Sway bars (front & rear)	8444X	Spring, shock, front (silver) (GTR) (progressive, 0.833 rate, white
8544	Trailing arm (2) (assembled with hollow balls)		stripe) (2)
8544X	Trailing arm, aluminum (blue-anodized) (2) (assembled with	8445A	Spring, shock, rear (blue) (GTR) (progressive, 1.042 rate) (2)
8544A	hollow balls) Trailing arm, aluminum (dark titanium anodized) (2) (assembled with hollow balls)	8445 8445X	Spring, shock, rear (natural finish) (GTR) (progressive, 1.042 rate) (2 Spring, shock, rear (silver) (GTR) (progressive, 1.042 rate) (2)
8544R	Trailing arm, aluminum (red-anodized) (2) (assembled with		Spur Gears & Pinion Gears
	hollow balls)	5647	Gear, 27-T pinion (0.8 metric pitch, compatible with 32-pitch) (fits
	Scale Details	5638	5mm shaft)/ set screw Gear, 31-T pinion (0.8 metric pitch, compatible with 32-pitch) (fit
8426	Batteries, black (2)	3030	5mm shaft)/ set screw
3422	Fire extinguisher, red (2)	5639	Gear, 34-T pinion (0.8 metric pitch, compatible with 32-pitch) (fit
3425	Floor jack & handle, grey	0==0	5mm shaft)/ set screw
8424 8421	Oil bottles, grey (2) Radiator, black	8573 8574	Gear, center differential, 47-tooth (spur gear) Gear, center differential, 51-tooth (spur gear)
8423	Shock reservoirs, black (2)	857 5	Gear, center differential, 51-tooth (spur gear)
0120	Shocks (GTR)		Steering Components
8452X	Body, GTR shock, 64mm, aluminum (blue-anodized) (front or	8543	Steering bellcranks/ servo saver/ servo saver spring/ servo spring
0 4 32A	rear, threaded)	0040	retainer/servo horn, steering
8453X	Body, GTR shock, 64mm, aluminum (blue-anodized) (front, no	8553	Stub axle, steel (use with #8550 driveshaft)
8452R	threads) Body, GTR shock, 64mm, aluminum (red-anodized) (front or rear,	8547 8547X	Toe links, front (2) (assembled with hollow balls) Toe links, front, Unlimited Desert Racer® (TUBES blue-anodized
0452D	threaded)		7075-T6 aluminum, stronger than titanium) (102mm) (2)
8453R	Body, GTR shock, 64mm, aluminum (red-anodized) (front, no threads)		(assembled with rod ends and hollow balls)/ aluminum wrench, 7mm (1)
8452	Body, GTR shock, 64mm, silver aluminum (front or rear, threaded)	8547A	Toe links, front, Unlimited Desert Racer® (TUBES dark titanium
8453	Body, GTR shock, 64mm, silver aluminum (front, no threads)		anodized, 7075-T6 aluminum, stronger than titanium) (102mm)
8462X	Body, GTR shock, 77mm, aluminum (blue-anodized) (rear, no threads)		(2) (assembled with rod ends and hollow balls)/ aluminum wrench, 7mm (1)
8462R	Body, GTR shock, 77mm, aluminum (red-anodized) (rear, no	8547R	Toe links, front, Unlimited Desert Racer® (TUBES red-anodized,
0.400	threads)		7075-T6 aluminum, stronger than titanium) (102mm) (2) (assembled with rod ends and hollow balls)/ aluminum wrench,
8462 7468X	Body, GTR shock, 77mm, silver aluminum (rear, no threads) Caps & spring retainers, GTR shock (upper cap (2)/ hollow balls (4)/		7mm (1)
, 1 00/	bottom cap (2)/ upper retainer (2)/ lower retainer (2))		Suspension Linkage
8458	Double seal kit, GTR shocks (x-rings (4)/ 4x6x0.5mm PTFE-coated washers (2)/ bottom caps (2)) (renews 2 shocks)	8542T	Suspension link, rear (upper) (aluminum, black-anodized) (10x206mm, center to center) (2) (assembled with hollow balls)
8455	Rebuild kit, GTR shocks (x-rings, bladders, pistons, piston nuts, shock rod ends) (renews 2 shocks)	8542A	Suspension link, rear (upper) (aluminum, blue-anodized) (10x206mm, center to center) (2) (assembled with hollow balls)
8456 8457	Shock caps, aluminum (black-anodized), Fox® Shocks (4)	8542R	Suspension link, rear (upper) (aluminum, red-anodized)
8457 8538	Shock caps, aluminum (blue-anodized), King® Shocks (4) Shock mounts, rear (left & right)	05409	(10x206mm, center to center) (2) (assembled with hollow balls)
8538X	Shock mounts, rear (left & right) (satin black chrome-plated)	8542X	Suspension link, rear (upper) (heavy duty, steel) (7x206mm, center to center) (2) (assembled with hollow balls)
8454	Shock shaft, 69mm (GTR) (front) (2)	8542	Suspension link, rear (upper) (steel) (4x206mm, center to center) (2)
8454T	Shock shaft, 69mm (GTR) (front) (TiN-coated) (2)		(assembled with hollow balls)
8463 8463T	Shock shaft, 74mm (GTR) (rear) (2) Shock shaft, 74mm (GTR) (rear) (TiN-coated) (2)	8546 8545	Suspension pin retainers (upper (2), lower (1))
8 4631 8464	Shock shaft, 74mm (GTR) (rear) (TiN-coated) (2) Shock shaft, 81mm (GTR) (rear) (2)	8545 8547	Suspension pin set (front) (3x51mm (2), 3x54mm (2), 3x93mm (2)) Toe links, front (2) (assembled with hollow balls)
8464T	Shock shaft, 81mm (GTR) (rear) (TiN-coated) (2)	8547X	Toe links, front, Unlimited Desert Racer® (TUBES blue-anodized
8451X	Shocks, GTR, 134mm, aluminum (blue-anodized) (fully assembled w/o springs) (front, no threads) (2)	A	7075-T6 aluminum, stronger than titanium) (102mm) (2) (assembled with rod ends and hollow balls)/ aluminum wrench,
8450X	Shocks, GTR, 134mm, aluminum (blue-anodized) (fully assembled w/o springs) (front, threaded) (2)	8547A	7mm (1) Toe links, front, Unlimited Desert Racer® (TUBES dark titanium
			anodized, 7075-T6 aluminum, stronger than titanium) (102mm)
8451R	Shocks, GTR, 134mm, aluminum (red-anodized) (fully assembled w/o springs) (front, no threads) (2)		(2) (assembled with rod ends and hollow balls)/ aluminum
8451R 8450R	w/o springs) (front, no threads) (2) Shocks, GTR, 134mm, aluminum (red-anodized) (fully assembled		(2) (assembled with rod ends and hollow balls)/ aluminum wrench, 7mm (1)
	w/o springs) (front, no threads) (2)		, , ,

ed 2.4GHz Radio & TSM (Model 85076-4) Parts List

Page 4	Unlimited Desert Racer: TQi Traxxas Link Enabled
8547R	Toe links, front, Unlimited Desert Racer® (TUBES red-anodized,
••••	7075-T6 aluminum, stronger than titanium) (102mm) (2)
	(assembled with rod ends and hollow balls)/ aluminum wrench,
8544	7mm (1) Trailing arm (2) (assembled with hollow balls)
8544X	Trailing arm, aluminum (blue-anodized) (2) (assembled with
••••	hollow balls)
8544A	Trailing arm, aluminum (dark titanium anodized) (2) (assembled
0E44D	with hollow balls)
8544R	Trailing arm, aluminum (red-anodized) (2) (assembled with hollow balls)
	Team Traxxas Items
2514	Decal sheet, racing sponsors
6160X	DVD, Maxx® Power! Full Throttle Action (sleeve)
9950	Official Team Traxxas® racing decal set (flag logo/ 6-color)
9909	Traxxas® racing banner, red & black (3x7 feet)
	Tires & Wheels
8472	Tires and wheels, assembled, glued (Desert Racer® wheels, black
0.475	with orange beadlock, BFGoodrich® Baja KR3 tires) (2)
8475	Tires and wheels, assembled, glued (Desert Racer® wheels, paddle tires, foam inserts) (2)
8474	Tires and wheels, assembled, glued (Method Race Wheels, black
	with red beadlock, BFGoodrich® Baja KR3 tires) (2)
8470	Tires, BFGoodrich® Baja KR3/ foam inserts (2)
8473 8471	Wheels, Desert Racer® (2) Wheels, Method Race (2)
0471	, , , , , ,
0504	Transmission Components
8591	Gearbox housing (includes upper housing, lower housing, & gear cover)
8592	Housing, planetary gears (front & rear halves)
8589	Output shaft, transmission/ x-ring
8588	Planetary gears (4)
8585	Ring gear, planetary
8593	X-ring seals, 6x9.6mm (4)
	Traxxas Tools
3433X	Body reamer (aluminum handle)
3433 3436	Body reamer (plastic handle) Cap, body reamer
3432	Scissors, curved tip
3431	Scissors, straight tip
8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes premium handle (medium), travel pouch, hex drivers (straight:
	1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm,
	and 8.0mm), 1/4" drive
8722	Speed bit handle, premium (rubber overmold)
8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end, includes premium handle (medium), travel pouch, hex drivers
	(straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm,
	2.5mm, 3.0mm), 1/4" drive
8719	Speed Bit Master Set, nut driver, 6-piece, includes premium
	handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4"
	drive
8716X	Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm, 3.0mm), 1/4" drive
8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm,
07.10	2.5mm), 1/4" drive
8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm,
0445	2.5mm, 3.0mm), 1/4" drive
3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm, 3.5mm, 4mm drivers/ 4mm, 5mm, 5.5mm, 7mm and 8mm nut
	drivers/ 2mm, 4mm, and 5mm slotted screwdrivers/ #00 Phillips,
	#0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrench/
	driver handle
	Turnbuckles & Threaded Rods
8547 8547X	Toe links, front (2) (assembled with hollow balls) Toe links, front, Unlimited Desert Racer® (TUBES blue-anodized,
00 -1 17	7075-T6 aluminum, stronger than titanium) (102mm) (2)
	(assembled with rod ends and hollow balls)/ aluminum wrench,
05474	7mm (1)
8547A	Toe links, front, Unlimited Desert Racer® (TUBES dark titanium anodized, 7075-T6 aluminum, stronger than titanium) (102mm)
	(2) (assembled with rod ends and hollow balls)/ aluminum
	wrench, 7mm (1)
8547R	Toe links, front, Unlimited Desert Racer® (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (102mm) (2)
	(assembled with rod ends and hollow balls)/ aluminum wrench,
	7mm (1)

If you have questions or need technical assistance, call Traxxas at:

1-888-TRAXXAS

(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com

TRAXXAS.COM