

5530

Bulkheads, front (upper & lower)

## Jato® (Model 55077-3) Parts List

	Air Filters	5520 5523	Bumper, rear (for use with mid-mounted RX battery) Chassis top plate
5265	Air filter housing/ foam insert/ Jato® air filter base (long, straight)/ cable tie (1-each) (TRX® 2.5)	5522	Chassis, 6061-T6 aluminum (3mm) (blue anodized)/ adhesive foam
5261 5263	Air filter inserts, foam (3) (pre-oiled) (TRX® 2.5) Air filter oil	5522X	pad (1) Chassis, 7075-T6 aluminum (3mm) (Titanium-anodized) (machined, lighter than stock)/ adhesive foam pad (1)
	Bearings & Bushings	5592	Clutch guard
4609	Ball bearings (5x10x4mm) (2) (metal shielded, for clutch bell)	5527	Dirt guards, chassis (left & right)
4611	Ball bearings (5x11x4mm) (2) (metal shielded, for clutch bell)	5560	Engine mount/ engine mount spacers (2)/ 3x15 CS with washers (4)/
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)	===.	4x18 BCS (2)/ flathead engine mount screws 3x10 (2)
5124	Ball bearings, blue rubber sealed (4x7x2.5mm) (2)	5581 5559	Gaskets, differential/transmission
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)	5559	Mounts, suspension pin (rear anti-squat blocks) (1.5, 2.25, 3.0 & 3.75 degree) (1 each)
5114	Ball bearings, blue rubber shield (5x8x2.5mm) (2)	5524	Receiver box cover (for chassis top plate)/ battery cover (mid chassis
5123 2545	Bellcrank bushings (plastic) (4x7x2.5mm) (4) Bushings (plastic) (5x8x2.5mm) (4)	5516	Roll Hoop (composite)/ EZ-Start® plug mount
2040		5583	Rubber plugs, charge jack, 2-speed adjustment (Jato®)
	Body & Accessories	5519	Servo mounts, steering (left & right)
1926	Antenna caps, vinyl (2)/ antenna spool	9461X	Wheels, wheelie bar, 6061-T6 aluminum (blue-anodized) (2)/
5526	Antenna crimp nut, aluminum (blue-anodized)/ antenna nut tool	9461G	5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2) Wheels, wheelie bar, 6061-T6 aluminum (green-anodized) (2)/
<b>5526R</b> 1726	Antenna crimp nut, aluminum (red-anodized)/ antenna nut tool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)	34010	5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2)
3935	Body clip (mounting clip), angled, 90-degrees (10)	9461A	Wheels, wheelie bar, 6061-T6 aluminum (orange-anodized) (2)/
3935A	Body clip (mounting clip), angled, 90-degrees (black) (10)		5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2)
1834	Body Clips (12) (standard size)	9461P	Wheels, wheelie bar, 6061-T6 aluminum (pink-anodized) (2)/
5514	Body mount, front	9461R	5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2) Wheels, wheelie bar, 6061-T6 aluminum (red-anodized) (2)/
5511R	Body, Jato® 3.3, ProGraphix® (replacement for the painted	34011	5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2)
	body) Graphics are painted, requires paint & final color application.)	3038	Wiring harness, on-board radio system (includes on/off switch and
5511T	Body, Jato®, orange (painted, decals applied)		charge jack)
5511A	Body, Jato®, red (painted, decals applied)		Clutch & Related Parts
5513X	Decal sheet, Jato® 3.3	4609	Ball bearings (5x10x4mm) (2) (metal shielded, for clutch bell)
2514	Decal sheet, racing sponsors	4611	Ball bearings (5x11x4mm) (2)
9950	Official Team Traxxas® racing decal set(flag logo/ 6-color)	4118	Clutch bell (18-tooth)/5x8x0.5mm fiber washer (2)/ 5mm e-clip
5512	Wing mounting hardware, (4x8mmCCS (aluminum)(3)/ 4x7mm flanged NL (3)		(requires 5x10x4mm ball bearings part 4609)
		4120	Clutch bell (20-tooth)/5x8x0.5mm fiber washer (2)/ 5mm e-clip (requires 5x11x4mm ball bearings part 4611)
	Brake Components	4122	Clutch bell (22-tooth)/5x8x0.5mm fiber washer (2)/ 5mm e-clip
5588	Brake cam		(requires 5x11x4mm ball bearings part 4611)
5567	Brake cam lever/ linkage rod/ bellcrank/ 4mm Ball Screw (1)/ 4mm Ball Cup (1)/ 3.0NL (1)/ 3X10 SS (1)	4124	Clutch bell, (24 tooth) / 5x8x0.5mm fiber washer (2)/ 5mm E-clip (requires #4611-ball bearings, 5x11x4mm (2))
5564A 5565	Brake disc (semi-metallic material)	4146X	Clutch shoes (2)/ spring
3303	Brake pads (2)/ brake disc hub/ 3X15 CS (partially threaded) (2)/2mm pin (1)/ 4mm e-clip (1)	3281	Cone, split beveled
5566	Input shaft (slipper shaft)/ slipper shaft spacer	1633	E-clips/ C-rings
5568	Linkage set, throttle & brake (Jato®) (includes servo horn, rod guides,	<b>6542X</b> 5244	Flywheel (large, knurled for use with starter boxes) Flywheel nut (TRX® 2.5 and 2.5R)
	brake spring, brake adjustment dial, rods (wires), throttle return	6542	Flywheel with magnet (35mm)
	spring, hardware)	1985	PTFE-coated Washers, 5x8x0.5mm (20) (use with ball bearings)
	Bumpers & Skidplates		Differential Components
5515X	Battery Box, bumper (rear) (includes battery case with bosses for	5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
5535	wheelie bar, cover, and foam pad) Bumper, front	5580	Cover, differential
5520	Bumper, rear (for use with mid-mounted RX battery)	5136X	Differential oil kit (1 each: 10K, 30K, 50K weights)
5185	Tires, rubber (2) (fits Traxxas® wheelie bar wheels)	5581	Gaskets, differential/transmission
5584	Wheelie bar/ rear skid (assembled) (fits Jato®, requires 5515X for	5582	Gear set, differential (output gears (2)/ spider gears (2)/ spider gear
	installation)	5570	shaft)  Goars, differential 38 T (1)/ differential drive goar 20 T/ side cover
4976 <b>5186A</b>	Wheels (4)/ Axles (2), for wheelie bar Wheels, aluminum (blue-anodized) (2)/ 5x8mm ball bearings (4)/	5579	Gears, differential 38-T (1)/ differential drive gear 20-T/ side cover plate (1)/ gasket (1)/ output gear seals (x-ring) (2)/ 2.5x8mmCCS (4)/
E40C	axles (2)/ rubber tires (2)	5130	5x10x.5mmTW (2) Oil, differential (100K wt) (0.7 oz (20cc))
5186	Wheels, aluminum (red-anodized) (2)/ 5x8mm ball bearings (4)/ axles (2)/ rubber tires (2)	5135	Oil, differential (10K wt) (1.7 oz (50cc))
9461X	Wheels, wheelie bar, 6061-T6 aluminum (blue-anodized) (2)/	5039	Oil, differential (500K wt) (0.7 oz (20cc))
	5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2)	5137	Oil, differential (50K wt) (1.7 oz (50cc))
9461G	Wheels, wheelie bar, 6061-T6 aluminum (green-anodized) (2)/	2524	Screws, 2.5x8 countersunk machine (hex drive) (6)
04644	5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2)	2577	Screws, 3x10mm button-head machine (hex drive) (6)
9461A	Wheels, wheelie bar, 6061-T6 aluminum (orange-anodized) (2)/ 5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2)		Driveline Components
9461P	Wheels, wheelie bar, 6061-T6 aluminum (pink-anodized) (2)/	5555	Carriers, stub axle (rear) (left & right)
	5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2)	5555X	Carriers, stub axle, (rear) 6061-T6 aluminum (titanium-anodized)
9461R	Wheels, wheelie bar, 6061-T6 aluminum (red-anodized) (2)/	5528	Differential output yokes (2)/yoke pins M3/12.5 (2)
	5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2)	5551	Driveshaft assembly (1), left or right (fully assembled, ready to install) M3/12.5mm yoke pin (1)
	Chassis & Attachments	5551X	Driveshafts, Jato® (steel constant-velocity) (lubed with inner and
5515X	Battery Box, bumper (rear) (includes battery case with bosses for		outer dust boots) (1 pair)
	wheelie bar, cover, and foam pad)	5150	E-clips, 1.5mm (24)
3039	Battery holder, 4-cell (no on/off switch) (for Jato® and others that use	5550	Half shaft set, left or right (internal splined half shaft/ external splined
	a male Futaba style connector)	5550	half shaft/ rubber boot/ metal U-ioints) (assembled with glued b

half shaft/ rubber boot/ metal U-joints) (assembled with glued boot) (2

Page 2	Jato®: TRX® 3.3, TQi™ 2.4GHz Radio System, Traxxas	Link™ V	Vireless Module, & TSM® (Model 55077-3) Parts List
2754	Stub axle pins (4)	5558	Tie bars (front & rear)
5553	Stub axles, (rear) (2)	5537	Wheel spindles, front (left & right) (2)
1654	Wheel hubs, hex (2)/ stub axle pins (2)	5537X	Wheel spindles, front, 7075-T6 aluminum, blue-anodized (left &
	Engine & Servo Mounts		right)
4859	CS 3x10 flathead (hex drive)		Fuel Tank & Line
5560	Engine mount/ engine mount spacers (2)/ 3x15 CS with washers (4)/	3935	Body clip (mounting clip), angled, 90-degrees (10)
2547	4x18 BCS (2)/ flathead engine mount screws 3x10 (2) Screws, 4x18mm countersunk machine (hex drive) (6)	<b>3935A</b> 3147X	Body clip (mounting clip), angled, 90-degrees (black) (10) Fuel line (610mm or 2ft)
5519	Servo mounts, steering (left & right)	5548	Fuel tank (75cc, complete)
00.10	Engine Components	3149A	Heat shield tubing, fiberglass (2) (black)
5238R	Cooling head, PowerTune (machined aluminum, blue- anodized)	5547	Pull ring (1)/ fuel tank cap (1)/ engine shut-off clamp (1)/ 3x10 BCS
32301	(TRX® 3.3), head protector (1), 3x6mm CCS (5)	554O	(1)  Robuild kit fuel tank (includes: a ring grommets (2) can apring
5270R	EZ-Start® 2, complete system with controller, drive unit, wiring	5549	Rebuild kit, fuel tank (includes: o-ring, grommets (2), cap spring, hardware)
3980	harness Glow plug wrench (Universal wrench)		Fuel, Lubricants & Supplies
3232X	Glow plug, super-duty (long-medium)/gasket	5263	Air filter oil
5228	Head protector, cooling head (1)/3x6mm CCS (5) (TRX® 3.3)	5001	Bottle, Fuel filler (500cc)
5290	Piston/Sleeve (Matched Set), Wrist Pin Clips(2) (TRX® 3.3)	3232X	Glow plug, super-duty (long-medium)/gasket
5211R	Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX® 2.5, 2.5R, 3.3)	5148 5130	Grease, white lithium Oil, differential (100K wt) (0.7 oz (20cc))
5277	Shaft, starter (TRX® 2.5 & 2.5R)	5135	Oil, differential (10K wt) (1.7 oz (50cc))
5170	Starter, recoil (complete with screws) (TRX® 2.5)	5136	Oil, differential (30K wt) (1.7 oz (50cc))
	Exhaust	5039	Oil, differential (500K wt) (0.7 oz (20cc))
5546	Hanger, metal (for tuned pipe)/ 4x8 BCS (1)/ 3x10 BCS (1)	5137	Oil, differential (50K wt) (1.7 oz (50cc))
5540	Header, exhaust (Jato®) (tubular aluminum, clear anodized) (TRX®	5001R	Rebuild kit, fuel filler bottle (includes bottle lid (1) and dispensing tube caps, rubber (2) (fits 8mm or 5/16" dispensing tube))
5050	2.5, 2.5R)	5070	Top Fuel®, 20% Nitro (gallon)
5256 <b>5245X</b>	O-ring, header 12.2x1mm (TRX® 2.5)  Pipe coupler, molded (black)/ exhaust deflecter (rubber, black)/	5020	Top Fuel®, 20% Nitro (quart)
3243A	cable ties, long (2)/ cable ties, short (2)	5080	Top Fuel®, 33% nitro (gallon)
5245	Pipe coupler, molded (blue)/ Exhaust deflecter (rubber, blue)/ cable	5030	Top Fuel®, 33% nitro (quart)
E140	ties, long (2)/ cable ties, short (2)		Hardware
5142	Screws, 3x15mm caphead machine (hex drive) (with split and flat washers) (6)	5526	Antenna crimp nut, aluminum (blue-anodized)/ antenna nut tool
5485	Tuned pipe, Resonator®, R.O.A.R. legal (dual-chamber,	<b>5526R</b> 3935	Antenna crimp nut, aluminum (red-anodized)/ antenna nut tool Body clip (mounting clip), angled, 90-degrees (10)
	enhances mid to high-rpm power) (for Jato®, N. Rustler®, N. 4-	3935A	Body clip (mounting clip), angled, 90-degrees (10)  Body clip (mounting clip), angled, 90-degrees (black) (10)
5483	Tec® with TRX® Racing Engines) Tuned pipe, Resonator®, R.O.A.R. legal (single-chamber,	1834	Body Clips (12) (standard size)
3403	enhances low to mid-rpm power) (for Jato®, N. Rustler®, N. 4-	4859	CS 3x10 flathead (hex drive)
	Tec® with TRX® Racing Engines)	5150	E-clips, 1.5mm (24)
5541X	Tuned pipe, Resonator®, R.O.A.R. legal, blue-anodized (aluminum,	1633 5477	E-clips/ C-rings Flat wrench, 5mm (blue anodized aluminum)
	single chamber) (fits Jato®, N. Rustler®, N. 4-Tec®, with TRX® Racing Engines)	5478	Flat wrench, 8mm (blue anodized aluminum)
	EZ Start 2 & Related parts	3980	Glow plug wrench (Universal wrench)
5280	Control box (complete) (EZ-Start® 2)	5476X 5475	Hex wrenches; 1.5mm, 2mm, 2.5mm, 3mm, 2.5 ball Multi-tool (plastic)
5281	Control box battery cover w/ belt clip (EZ Start 2)	5158	Nuts, 2.5mm nylon locking (12)
5273	Cush-drive elements (4) (EZ Start 2)	2745	Nuts, 3mm nylon locking (12)
4583	EZ Start 2 wiring harness (for Jato®)	1747P	Nuts, 4mm flanged nylon locking (aluminum, pink anodized) (4)
5270R	EZ-Start® 2, complete system with controller, drive unit, wiring harness	3647	Nuts, 4mm flanged nylon locking (steel, serrated) (8)
5276	Gear set (complete) (EZ-Start® 2)	1747 <b>1747R</b>	Nuts, 4mm nylon locking (10)
5148	Grease, white lithium	1747K	Nuts, aluminum, flanged, serrated (4mm) (blue-anodized) (4) Nuts, aluminum, flanged, serrated (4mm) (green-anodized) (4)
5275	Housing set (inner, outer)/ 3x12mmBCS (5)/ 3x20BCS (1)/ motor	1747T	Nuts, aluminum, flanged, serrated (4mm) (orange-anodized) (4)
4504V	bushing (EZ-Start® 2)	1747A	Nuts, aluminum, flanged, serrated (4mm) (red-anodized) (4)
4581X	Lead wire, glow plug (blue) (EZ-Start® and EZ-Start® 2)/ molex pin extractor (use where glow plug wire does not have bullet connector)	3229	Screws, 2.5x10mm cap-head machine (hex drive) (6)
5279	Motor (hi-torque)/ pinion gear/ motor bushing (EZ-Start® 2)	2524	Screws, 2.5x8 countersunk machine (hex drive) (6)
5211R	Roller clutch/ 6x8x0.5 TW (1) (also called one-way bearing) (TRX®	5169 2674	Screws, 2.6x8mm countersunk machine (6) (EZ Start 2 motor) Screws, 2x6mm roundhead self-tapping (6)
E460	2.5, 2.5R, 3.3)	2577	Screws, 3x10mm button-head machine (hex drive) (6)
5169 5282	Screws, 2.6x8mm countersunk machine (6) (EZ Start 2 motor) Screws, 3x12mm button-head machine (6) (Starter attachment	5282	Screws, 3x12mm button-head machine (6) (Starter attachment
0202	screws w/ threadlock)	2578	screws w/ threadlock)
2578	Screws, 3x12mm button-head machine (hex drive) (6)	2579	Screws, 3x12mm button-head machine (hex drive) (6) Screws, 3x15mm button-head machine (hex drive) (6)
5277	Shaft, starter (TRX® 2.5 & 2.5R)	5142	Screws, 3x15mm caphead machine (hex drive) (with split and flat
	Front Suspension		washers) (6)
5530	Bulkheads, front (upper & lower)	2553	Screws, 3x15mm countersunk machine (6) (hex drive)
5536	Caster blocks, 25-degree (left & right)/ steering blocks, 25- degree (left & right)	2583 2580	Screws, 3x18 button-head machine (hex drive) (6) Screws, 3x20mm button-head machine (hex drive) (6)
5532	Caster blocks, 30-degree (left & right)/ steering blocks, 30-degree (left	2575	Screws, 3x6mm button-head machine (hex drive) (6)
	& right)	2554	Screws, 3x6mm caphead machine (hex drive) (6)
5525	Rod ends (12)/ hollow balls (12)	3932	Screws, 3x6mm flat-head machine (hex drive) (6)
5525R	Rod ends, heavy duty (Jato®/Slayer) (8)	2550	Screws, 3x8mm countersunk machine (6) (hex drive)
5529	Shim set (for adjusting Jato roll center)/ hollow balls (for inner camber links) (4)	2535 3937	Screws, 4x10mm countersunk machine (hex drive) (6) Screws, 4x12mm button-head machine (hex drive) (6)
5518	Shock tower, front	2547	Screws, 4x12mm button-nead machine (nex drive) (6) Screws, 4x18mm countersunk machine (hex drive) (6)
5531	Suspension arms, front (left & right)	3940	Screws, 4x4 button-head machine, aluminum (blue) (hex drive) (6)
5521	Suspension pin set, complete (hardened steel, front & rear), 3x27mm	4897	Screws, set (grub) 4mm (6) (w/ threadlock)
EEOUA	(4) 3x35(2), 3x52mm (4) Sway har kit (front and roar) (includes sway hars and linkage)	3967	Shoulder screws 3x10 (6) (without threadlock)
5589X 5596	Sway bar kit (front and rear) (includes sway bars and linkage) Sway bars (front) (includes Soft, Medium, Hard)	5149 5534	Spacers, steel (Jato® twin-spoke wheels, front) (4)
5550	and from the financial cont, modium, main	JJJ4	Spacers, stub axle carrier (rear)

4147 5512	Wheel nuts, 5mm nylon locking (8) Wing mounting hardware, (4x8mmCCS (aluminum)(3)/ 4x7mm		Recoil Starter
5512	Wing mounting hardware, (4x8mmCCS (aluminum)(3)/ 4x7mm flanged NL (3)	5277	Shaft, starter (TRX® 2.5 & 2.5R)
	Radio System, Batteries & Chargers	5170	Starter, recoil (complete with screws) (TRX® 2.5)
0010	1800mAh 7.2V 6-cell flat NiMH Battery, Power Cell		Shock Oil
2919 <b>3028</b>	Adapter, Molex to Traxxas® receiver battery pack (for charging)	5031	Oil, shock (20 wt, 200 cSt, 60cc) (silicone)
,020	(1)	5032	Oil, shock (30 wt, 350 cSt, 60cc) (silicone)
726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)	5033	Oil, shock (40 wt, 500 cSt, 60cc) (silicone)
3548	Battery door, TQ 2.4 transmitter (replacement for #6516, 6517	5034	Oil, shock (50 wt, 600 cSt, 60cc) (silicone)
8039	transmitter) Battery holder, 4-cell (no on/off switch) (for Jato® and others that use	5035 5036	Oil, shock (60 wt, 700 cSt, 60cc) (silicone) Oil, shock (70 wt, 900 cSt, 60cc) (silicone)
0039	a male Futaba style connector)	5037	Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone)
2914	Battery, Power Cell AA Alkaline (4)	5029	Shock oil bottle (60cc) (for mixing shock oil)
3036	Battery, RX Power Pack (5-cell flat style, GP cells, NiMH, 1200mAh)	5038X	Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, & 80 wt premium shock oils with spinning carousel rack)
2977	Charger, D/C, 2 amp (Molex) (5 - 6 cell, 6.0 - 7.2 volt, NiMH)	5038	Spinning carousel rack
6525 2978	Communication link, telemetry expander Fuse, D/C charger, 5A (2) (for #2974, 2975, 2977)		Shocks (GTR)
2010	Gear set (for 2018 servo)	5467A	Body, GTR shock (aluminum, blue-anodized) (1)
2053	Gear set (for 2055, 2056 servos)	5466X	Body, GTR shock (hard-anodized, PTFE-coated aluminum) (1)
6555	Mount, telemetry expander (fits Slash 4X4, Stampede® 4X4,	5467 5465	Body, GTR shock (molded composite) (2) Caps and spring retainers, GTR shock (upper cap (2)/ hollow balls
8526	Rally, Jato®) Mounts RDM concer (pitro engines)/ 3v10 CS with aplit and flat	0-100	(2)/ bottom cap (2)/ upper retainer (2)/ lower retainer (2))
6536	Mounts, RPM sensor (nitro engines)/ 3x10 CS with split and flat washers (2)	5464	Dust boot, shock (expandable, seals and protects shock shaft)(1
5533	Receiver, micro, TQi 2.4GHz with telemetry & TSM® (5-channel)	E 435	pair)
6552	Seal kit, expander box (includes o-ring, seals, and silicone	5475 5158	Multi-tool (plastic) Nuts, 2.5mm nylon locking (12)
	grease)	5562	Rebuild kit, GTR composite shocks (x-rings, bladders, all pistons,
6526 6527	Sensor, auto-detectable, temperature Sensor, auto-detectable, voltage	5502	piston nuts, shock rod ends) renews 2 shocks
5522	Sensor, RPM (short)/ 3x4mm BCS (1)/ 3x4mm GS (1)	5469	Rod ends (GTR shocks)
3521	Sensor, temperature and voltage (long)	5463	Shaft, GTR shock (2) (stainless)
2052	Servo case (for 2055 servo)	5463T	Shaft, GTR shock TiN-coated (2)
2075R	Servo, digital high-speed, metal gear (ball bearing), waterproof	5460 5460A	Shocks, GTR (assembled) (2) (without springs) Shocks, GTR aluminum, blue-anodized bodies with TiN shafts
2070	Servo, digital high-torque (ball bearing)	04007	(fully assembled w/o springs) (4)
2075 2075X	Servo, digital high-torque (ball bearing), waterproof	5460R	Shocks, GTR aluminum, red-anodized bodies with TiN shafts
207 <b>5X</b> 2055	Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, high-torque	FF04	(fully assembled w/o springs) (4)
2056	Servo, high-torque, waterproof (blue case)	5561 <b>5460X</b>	Shocks, GTR composite (assembled) (2) (without springs)  Shocks, GTR hard-anodized, PTFE-coated aluminum bodies with
6553X	Telemetry Expander 2.0 and GPS module 2.0, TQi radio system	JHOUA	TiN shafts (fully assembled w/o springs) (4)
6550X	Telemetry expander 2.0, TQi radio system (for use only with #6551X GPS module)	5461	Variable damping kit, GTR shocks (includes #1, #2, #3 pistons
6551X	Telemetry GPS module 2.0, TQi radio system (for use only with #6550X telemetry expander)		and stainless steel valves) Slipper Clutch Components
6507R	TQi 2.4 GHz High Output radio system, 4-channel with Traxxas®	5478	Flat wrench, 8mm (blue anodized aluminum)
	Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver)	5552A	Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (2)/ pin/ 4.0mm NL (1)/ 5.0mm NL (1))
6528	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2- channel (transmitter only)	2554	Screws, 3x6mm caphead machine (hex drive) (6)
6529	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 3-	5556	Slipper pressure plate & hub (aluminum alloy)
	channel (transmitter only)	F ( ) =	Springs
6530	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4-	5427 5428	Spring, shock (GTR) (front 0.7 yellow) (1 pair) Spring, shock (GTR) (front) (0.9 rate orange) (1 pair)
6511	channel (transmitter only) Traxxas® Link Bluetooth® module	5428 5432	Spring, shock (GTR) (front) (0.9 rate orange) (1 pair) Spring, shock (GTR) (front) (1.3 rate gold) (1 pair)
3038	Wiring harness, on-board radio system (includes on/off switch and	5429	Spring, shock (GTR) (rear) (1.0 rate tan) (1 pair)
	charge jack)	5431	Spring, shock (GTR) (rear) (1.2 rate silver) (1 pair)
2734	Zip Ties (small)	5430	Spring, shock (GTR) (std. front) (1.1 rate green) (1 pair)
	Ready-To-Race Model	5433 5433 A	Spring, shock (GTR) (std. rear) (1.4 rate pink) (1 pair)
55077-3	Jato® 3.3: 1/10 Scale 2-Speed Nitro-Powered 2WD Stadium Truck	5433A 5434A	Spring, shock (red) (GTR) (1.4 rate double pink stripe) Spring, shock (red) (GTR) (1.6 rate double blue stripe) (1 pair)
	with TQi™ 2.4GHz Radio System, Traxxas Link™ Wireless Module,	5434A 5940	Spring, shock (red) (GTR) (1.8 rate double blue stripe) (1 pair)
	and Traxxas Stability Management (TSM)®	5941	Spring, shock (red) (GTR) (2.0 rate double black stripe) (1 pair)
	Rear Suspension	5942	Spring, shock (red) (GTR) (2.3 rate double purple stripe) (1 pair)
5555	Carriers, stub axle (rear) (left & right)	5434	Spring, shock (white) (GTR) (1.6 rate blue) (1 pair)
5555X	Carriers, stub axle, (rear) 6061-T6 aluminum (titanium-anodized)		Spur Gears & Clutch Bells
5559 5525	Mounts, suspension pin (rear anti-squat blocks) (1.5, 2.25, 3.0 & 3.75 degree) (1 each) Rod ends (12)/ hollow balls (12)	4118	Clutch bell (18-tooth)/5x8x0.5mm fiber washer (2)/ 5mm e-clip (requires 5x10x4mm ball bearings part 4609)
5525R	Rod ends, heavy duty (Jato®/Slayer) (8)	4120	Clutch bell (20-tooth)/5x8x0.5mm fiber washer (2)/ 5mm e-clip
5529	Shim set (for adjusting Jato roll center)/ hollow balls (for inner camber links) (4)	4122	(requires 5x11x4mm ball bearings part 4611) Clutch bell (22-tooth)/5x8x0.5mm fiber washer (2)/ 5mm e-clip
5517	Shock tower, rear	4124	(requires 5x11x4mm ball bearings part 4611) Clutch bell, (24 tooth) / 5x8x0.5mm fiber washer (2)/ 5mm E-clip
5534	Spacers, stub axle carrier (rear)	7144	(requires #4611-ball bearings, 5x11x4mm (2))
5553	Stub axles, (rear) (2)	2554	Screws, 3x6mm caphead machine (hex drive) (6)
5533 5521	Suspension arms, rear (left & right) Suspension pin set, complete (hardened steel, front & rear), 3x27mm	3956	Spur gear, 54-tooth (0.8 metric pitch, compatible with 32-pitch)
JJZ 1	(4) 3x35(2), 3x52mm (4)	3957	Spur gear, 56-tooth (0.8 metric pitch, compatible with 32-pitch)
5589X 5597	Sway bars (front and rear) (includes sway bars and linkage) Sway bars (rear) (includes Soft, Medium, Hard)	3958	Spur gear, 58-tooth (0.8 metric pitch, compatible with 32-pitch)
5558	Tie bars (front & rear)		
5557	Tie bars (rear) (3 & 5-degree toe adjustment)		

5557

Tie bars (rear) (3 & 5-degree toe adjustment)

	Steering Components	5149	Spacers, steel (Jato® twin-spoke wheels, front) (4)
5123	Bellcrank bushings (plastic) (4x7x2.5mm) (4)	2754 5577R	Stub axle pins (4) Tires & wheels, assembled, glued (All Star chrome wheels,
5544 <b>5542X</b>	Bellcrank posts (steering)(2)  Drag link, machined 6061-T6 aluminum (blue-anodized)/ 5x8x2.5	3777A	Anaconda® tires, foam inserts) (nitro front) (1 Left, 1 Right)  Tires & wheels, assembled, glued (All-Star black chrome wheels,
5355X	ball bearing (2) Hollow ball set, aluminum Revo® (30)/ tall centered hollow ball	3776A	Anaconda® tires, foam inserts) (nitro front) (1 left, 1 right) Tires & wheels, assembled, glued (All-Star black chrome wheels,
5545	(2)/ tall offset hollow ball (2)/ bump steer adjustment shims; 3.5mm (2), 1.17mm (2) Servo horn, steering/ linkage, steering (3x30 threaded rod)/ rod ends	55700	Anaconda® tires, foam inserts) (nitro rear/ electric front) (1 left, 1 right)
5545X	(2)/ hollow balls (2)  Servo horns, steering and throttle (for non-Traxxas® servos	5576R	Tires & wheels, assembled, glued (All-Star chrome wheels, Anaconda® tires, foam inserts) (nitro rear/ electric front) (1 left, 1 right)
2055	(Hitec, JR, KO, Airtronics)) Servo, high-torque	5573	Tires & wheels, assembled, glued (Jato® twin-spoke wheels, Victory tires, foam inserts) (rear) (2)
5543	Steering bellcranks/ servo saver/ servo saver spring/ steering	5569	Tires, Alias 2.8" (soft-compound) (rear) (2)/ foam inserts (2)
== 10	support/ 4x7x2.5 PB (4)/ 5x0.8mm NL (1)	5578	Tires, Anaconda® 2.8" (2)/ foam inserts (2)
5542	Steering drag link/ 3x10mm shoulder screws (without threadlock) (2)	5563	Tires, ribbed 2.8" (front) (2)/ foam inserts (2)
5594	Turnbuckle, aluminum (red-anodized), camber link, 58mm (1)(assembled with rod ends, hollow balls in separate bag)(see part 5539X for complete set of Jato® aluminum turnbuckles)	4790R 5570	Tires, Spiked 2.2 (R(2) (Soft Compound) w/inserts Tires, Victory 2.8" (rear) (2)/ foam inserts (2)
5595	Turnbuckle, aluminum (red-anodized), front toe link, 61mm (1)	4174	TRX® Pro-Star chrome wheels (2) (front) (for 2.2" tires)
	(assembled with rod ends and hollow balls)(see part 5539X for	4172	TRX® Pro-Star chrome wheels (2) (rear) (for 2.2" tires)
	complete set of Jato® aluminum turnbuckles)	1654 <b>1654X</b>	Wheel hubs, hex (2)/ stub axle pins (2) Wheel hubs, hex (blue-anodized, lightweight aluminum) (2)/ axle
5539X	Turnbuckles, aluminum (red-anodized), camber links, 58mm (4)/ front toe links, 61mm (2) (assembled with rod ends and hollow	5576	pins(2) Wheels, All Star 2.8" (chrome) (rear) (2)
5530	balls)/ aluminum 5mm wrench (red-anodized) Turnbuckles, toe-links, 61mm (front or rear) (2) (assembled with rod	5577A	Wheels, All-Star 2.8" (black chrome) (nitro front) (2)
5538	ends and hollow balls)	5576A	Wheels, All-Star 2.8" (black chrome) (nitro rear / electric front) (2)
	Suspension Linkage	5572	Wheels, Jato® twin-spoke 2.8" (chrome) (rear) (2)
5529X	Ball studs, aluminum, hard-anodized, PTFE-coated (4) (use for		Transmission Components
5355X	inner camber link mounting) Hollow ball set, aluminum Revo® (30)/ tall centered hollow ball	5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
3333X	(2)/ tall offset hollow ball (2)/ bump steer adjustment shims;	5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
	3.5mm (2), 1.17mm (2)	5592	Clutch guard
5525	Rod ends (12)/ hollow balls (12)	5581	Gaskets, differential/transmission
5525R	Rod ends, heavy duty (Jato®/Slayer) (8)	5585	Gear set, 2-speed (2nd speed gear, 29T/ input gear, 17T steel)
5521	Suspension pin set, complete (hardened steel, front & rear), 3x27mm	5586	Gear, 1st speed 32T/ input gear 14T
5594	(4) 3x35(2), 3x52mm (4) Turnbuckle, aluminum (red-anodized), camber link, 58mm	5591 5566	Gearbox halves (right & left)
3334	(1)(assembled with rod ends, hollow balls in separate bag)(see	5593	Input shaft (slipper shaft)/ slipper shaft spacer Primary shaft/ 1st speed hub/one-way bearing/ snap ring/ 5x8x0.5
	part 5539X for complete set of Jato® aluminum turnbuckles)	0000	TW
5595	Turnbuckle, aluminum (red-anodized), front toe link, 61mm (1) (assembled with rod ends and hollow balls)(see part 5539X for	5583 <b>5593X</b>	Rubber plugs, charge jack, 2-speed adjustment (Jato®) Single speed conversion kit (eliminates the 2-speed, makes
FERRY	complete set of Jato® aluminum turnbuckles)		Jato® race legal).
5539X	Turnbuckles, aluminum (red-anodized), camber links, 58mm (4)/ front toe links, 61mm (2) (assembled with rod ends and hollow		Traxxas Tools
	balls)/ aluminum 5mm wrench (red-anodized)	3433X	Body reamer (aluminum handle)
5539	Turnbuckles, camber links, 58mm (assembled with rod ends and	3433	Body reamer (plastic handle)
	hollow balls) (2)	3436	Cap, body reamer
5538	Turnbuckles, toe-links, 61mm (front or rear) (2) (assembled with rod	3432	Scissors, curved tip
	ends and hollow balls)	3431 8712	Scissors, straight tip
	Team Traxxas Items	0/12	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes premium handle (medium), travel pouch, hex drivers (straight:
9916	Backpack, RC car carrier, 12" x 12" x 24" (fits TRX-4 & similar)		1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm,
2514	Decal sheet, racing sponsors		and 8.0mm), 1/4" drive
9917	Duffel bag, medium, 30" x 12" x 12" (fits 1/10 Slash®, TRX-4®, & similar)	8722	Speed bit handle, premium (rubber overmold)
9950	Official Team Traxxas® racing decal set(flag logo/ 6-color)	8710	Speed Bit Master Set, hex and nut driver, 13-piece, includes premium handle (medium), travel pouch, hex drivers (straight:
9909	Traxxas® racing banner, red & black (3x7 feet)		1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm,
	Throttle & Brake Linkage		3.0mm), and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm,
5588	Brake cam		8.0mm), 1/4" drive
5567	Brake cam lever/ linkage rod/ bellcrank/ 4mm Ball Screw (1)/ 4mm Ball Cup (1)/ 3.0NL (1)/ 3X10 SS (1)	8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end, includes premium handle (medium), travel pouch, hex drivers (straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm,
5568	Linkage set, throttle & brake (Jato®) (includes servo horn, rod guides, brake spring, brake adjustment dial, rods (wires), throttle return	8719	2.5mm, 3.0mm), 1/4" drive  Speed Bit Master Set, nut driver, 6-piece, includes premium
5545X	spring, hardware) Servo horns, steering and throttle (for non-Traxxas® servos		handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
4056	(Hitec, JR, KO, Airtronics)) Spring, throttle return (2) (Jato®, T-Maxx® 2.5R, 3.3)	8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" drive
1000	Tires & Wheels	8716X	Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm,
4611	Ball bearings (5x11x4mm) (2)		3.0mm) 1/4" drive
4607	Ball bearings (5x11x4mm) (8)	8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm,
1974	Lite-wheels, dished (2) (front)	0= 1=	2.5mm), 1/4" drive
1972	Lite-wheels, dished (2) (rear)	8715X	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm,
1747P	Nuts, 4mm flanged nylon locking (aluminum, pink anodized) (4)	8714	2.5mm, 3.0mm), 1/4" drive Speed Bit Set, screwdriver, 3-piece straight (3mm slotted, #1
3647	Nuts, 4mm flanged nylon locking (steel, serrated) (8)	U/ 17	Phillips, and #2 Phillips bits), 1/4" drive
1747	Nuts, 4mm nylon locking (10)	3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm,
1747R	Nuts, aluminum, flanged, serrated (4mm) (blue-anodized) (4)		3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut
1747G 1747T	Nuts, aluminum, flanged, serrated (4mm) (green-anodized) (4) Nuts, aluminum, flanged, serrated (4mm) (orange-anodized) (4)		drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips,
17471 1747A	Nuts, aluminum, flanged, serrated (4mm) (transperantolized) (4)		#0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm wrenches/ driver handle)
	,		

Page 5 Jato®: TRX® 3.3, TQi™ 2.4GHz Radio System, Traxxas Link™ Wireless Module, & TSM® (Model 55077-3) Parts List

	Turnbuckles & Threaded Rods
5477	Flat wrench, 5mm (blue anodized aluminum)
5545	Servo horn, steering/ linkage, steering (3x30 threaded rod)/ rod ends (2)/ hollow balls (2)
5594	Turnbuckle, aluminum (red-anodized), camber link, 58mm (1)(assembled with rod ends, hollow balls in separate bag)(see part 5539X for complete set of Jato® aluminum turnbuckles)
5595	Turnbuckle, aluminum (red-anodized), front toe link, 61mm (1) (assembled with rod ends and hollow balls)(see part 5539X for complete set of Jato® aluminum turnbuckles)
5539X	Turnbuckles, aluminum (red-anodized), camber links, 58mm (4)/ front toe links, 61mm (2) (assembled with rod ends and hollow balls)/ aluminum 5mm wrench (red-anodized)
5539	Turnbuckles, camber links, 58mm (assembled with rod ends and hollow balls) (2)
5538	Turnbuckles, toe-links, 61mm (front or rear) (2) (assembled with rod ends and hollow balls)
	Two-Speed Components
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
5585	Gear set, 2-speed (2nd speed gear, 29T/ input gear, 17T steel)
5586	Gear, 1st speed 32T/ input gear 14T
5590	Primary clutch assembly (2-speed shift hub)
5583	Rubber plugs, charge jack, 2-speed adjustment (Jato®)

If you have questions or need technical assistance, call Traxxas at:

1-888-TRAXXAS

(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com

TRAXXAS.COM