

(Aeropoxy Resin used with BD1 Aeropoxy Hardener)

Page: 1/7

**Compilation date:** 28/10/2020 **Revision No:** 2 **date** 5/05/2021

# Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name: Aeropoxy Resin

REACH registered number(s): BIS A-01-2119456619-26/BIS F-01-2119454392-40/ALIPHATIC GLYCIDYL ETHER-01-

2119485289-22

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Model hobby builds

# 1.3. Details of the supplier of the safety data sheet

Company name: Deluxe Materials Ltd.,

Unit 13, Cufaude Business Park

Cufaude Lane, Bramley, Hampshire RG26 3EN United Kingdom

Telephone: +44(0)1256 883944

Email: john@deluxematerials.com

**1.4. Emergency telephone number:** +44(0)1256 883944 9-5.30pm office hours only

# **Section 2: Hazards identification**

# 2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317

Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Toxic to aquatic life with long lasting effects.

# 2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS07: Exclamation mark

GHS09: Environmental





Signal words: Warning

(Aeropoxy Resin used with BD1 Aeropoxy Hardener)

Page: 2

Precautionary statements: P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P321: Specific treatment (see instructions on this label)

#### 2.3. Other hazards

Other hazards: Not classified as flammable but will burn.

PBT: This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

#### 3.2. Mixtures

# **Hazardous ingredients:**

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT} - REACH registered number(s): 01-2119456619-26

EINECS	CAS	PBT / WEL	CLP Classification	Percent
500-033-5	25068-38-6	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	50-70%

# BISPHENOL F EPICHLOROHYDRIN RESIN WITH NUMBER AVERAGE - REACH registered number(s): 01-2119454392-40

500-006-8	9003-36-5	-	Skin Irrit. 2: H315; Skin Sens. 1: H317;	10-30%
			Aquatic Chronic 2: H411; Eye Irrit. 2:	
			H319	

### ALIPHATIC GLYCIDYLETHER - REACH registered number(s): 01-2119485289-22-XXXX

271-846-8	68609-97-2	-	Skin Irrit. 2: H315; Skin Sens. 1: H317;	10-30%
			Aquatic Chronic 2: H411; Eye Irrit. 2:	
			H319	

Contains: Blend of liquid epoxy resin(s) and a reactive diluent.

#### Section 4: First aid measures

# 4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

(Aeropoxy Resin used with BD1 Aeropoxy Hardener)

Page: 3

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

# Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

### Section 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid.

# 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

# 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

(Aeropoxy Resin used with BD1 Aeropoxy Hardener)

Page: 4

# 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the

storage room must be impermeable to prevent the escape of liquids.

# 7.3. Specific end use(s)

Specific end use(s): No data available.

### Section 8: Exposure controls/personal protection

# 8.1. Control parameters

Workplace exposure limits: No data available.

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

#### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be

impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

# Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale yellow

Odour: Barely perceptible odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: 11.6 mg/l @ 20°C

Viscosity: 0,7 - 1,1 Pa.s : 25°C ASTM D-445

Boiling point/range°C: 150°C Flash point°C: >150

Part.coeff. n-octanol/water: Not determined Autoflammability°C: ca.400°C

**Vapour pressure:** <0.1 mbar at 20°C **Relative density:** 1.120kg/m3 at 25°C

**pH**: 6 - 8

#### 9.2. Other information

Other information: No data available.

(Aeropoxy Resin used with BD1 Aeropoxy Hardener)

Page: 5

# Section 10: Stability and reactivity

# 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat.

#### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# **Section 11: Toxicological information**

### 11.1. Information on toxicological effects

# **Toxicity values:**

Route	Species	Test	Value	Units
ORL	-	LD50	>2000	mg/kg
SKN	-	LD50	>2000	mg/kg

### Hazardous ingredients:

# **BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}**

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

# Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation OPT		Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

# Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

(Aeropoxy Resin used with BD1 Aeropoxy Hardener)

**Page**: 6

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

# **Section 12: Ecological information**

### 12.1. Toxicity

Ecotoxicity values: No data available.

#### 12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

#### 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

# 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

# 12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

# Section 13: Disposal considerations

# 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Disposal of packaging: Drain container thoroughly. Rinse three times with suitable solvent Treat rinsings as for

product disposal. After draining, vent in a safe place away from sparks and fire Where practical, containers and packaging should be recycled by a licensed contractor. Arrange

for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

# **Section 14: Transport information**

# 14.1. UN number

UN number: UN3082

### 14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(LIQUID EPOXY RESIN)

(Aeropoxy Resin used with BD1 Aeropoxy Hardener)

Page: 7

# 14.3. Transport hazard class(es)

Transport class: 9

#### 14.4. Packing group

Packing group: III

#### 14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: Yes

# 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E
Transport category: 3

# **Section 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

# **Section 16: Other information**

#### Other information

Other information: Notification status:

EU - EINECS List : On or in compliance with the inventory.

USA - TSCA : Included on Inventory

IECSC : All components listed.

Philippines - PICCS : Included on Inventory.

Phrases used in s.2 and s.3: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.