

Safety Data Sheet: BD13 Fibreglass Cloth 1.5 oz



Revision 2

1st Issue Date: 13/10/2021

2nd Issue Date: 18.10.2022

Section 1: Identification of the Substance/Preparation and of the Company undertaking

Identification of the substance or preparation:

Product: Fibreglass
Product Code: BD13
Product Type: Continuous filament E-glass.
Application: Modelling uses.

1.2 Company/undertaking identification:

Deluxe Materials Ltd., Unit 12 & 13, Cufau de Business Park, Cufau de Lane, Bramley, Hampshire, RG26 5DL,
United Kingdom Telephone: +44 (0)1256 883944 E-mail: john@deluxematerials.com

Section 2: Composition/Information on Ingredients

Ingredients: A typical composition of E-glass is as follows: -
SiO₂ (Silicon Dioxide) 54.2%
Al₂O₃ (Aluminium Oxide) 15.2%
CaO (Calcium Oxide) 17.3%
B₂O₃ (Boron Oxide) 8.0%
MgO (Magnesium Oxide) 4.7%
Na₂O (Sodium Oxide) 0.6%

Section 3: Hazards Identification

Chronic: None known.
Acute: Man made mineral fibres (MMMF) can cause irritation to the skin and eyes. It may also irritate the mucous membranes and upper respiratory tract in excessively dusty conditions.

Section 4: First-Aid Measures

Eye Contact: Flush eyes with running water for at least 15 minutes, including under eyelids. Do not rub or scratch the eyes. Seek medical attention if irritation persists.
Skin Contact: Wash with copious amounts of cold water and some soap. Warm water will open the pores of the skin which will cause further penetration of the fibres. Do not rub or scratch affected areas. Seek medical attention if irritation persists.
Inhalation: Move person to fresh air. Seek medical attention if irritation persists.
Ingestion: Ingestion is unlikely, if it does occur, observe the individual for several days to insure that intestinal blockage does not occur.

Section 5: Fire-Fighting Measures

Extinguishing Media: No limitations with regard to fire extinguishers.
Protective Measures: N/A
Fire & Explosion Hazards: None

Section 6: Accidental Release Measures

Land Spill: Scoop up material and place in a suitable container for disposal as non-hazardous waste. Avoid dry sweeping. If available use an industrial vacuum cleaner with high efficiency filter.
Water Spill: The material will settle. It is non-hazardous in water.
Air release: This material settles out of the air and can be concentrated on land to dispose of as a non-hazardous material.

Section 7: Handling and Storage

7.1. Handling

Precautions: Employees should be instructed in good work practices in order to minimise generation of and exposure to dust. Avoid contact with the skin and eyes, wear appropriate personal protection equipment (PPE). The skin should first be rinsed with copious amounts of cold water before the application of soap to prevent aggravation of the skin by fibres.

7.2. Storage

Precautions: Standard warehousing conditions are applicable.

Section 8: Exposure Controls/Personal Protection

8.1 Exposure Controls

Occupational Exposure Limit: The (UK) Health & Safety Executive enforce an occupational exposure limit as a Maximum Exposure Limit of 5mg/m³ as measured by personal (breathing zone) monitoring.

Engineering Measures: Where particularly dusty operations are unavoidable control of dust should primarily be by engineering control, where this is practicable.

8.2 Personal

Respiratory Protection: On some occasions respiratory protective equipment may be the only reasonable practical precaution which can be taken to protect the respiratory system. Respiratory protective equipment should conform to BS 2091, BS 4558, BS 4771 or BS 6016, dependent upon the concentration of dust and the length of exposure time.

Skin, Eyes, Other: For employees handling this material standard protective equipment should be routinely supplied for protecting the skin. Safety glasses, goggles or face shields may be needed in some circumstances.

Section 9: Physical and Chemical Properties

Appearance: Comprises of E-glass continuous fibre yarn. The mean diameter of the fibre ranges from 8-12 microns for yarn based products and 18-25 microns for roving based products.

Odour, Flash Point, Solubility: N/A

Section 10 Stability and Reactivity

Stability: Stable

Conditions to avoid: None

Incompatibility: None

Hazardous Decomposition

Products: None

Section 11: Toxicological Information

Acute Effects: There are no known acute effects.

Chronic Effects: This material is not expected to have any chronic (long-term) effect.

Section 12: Ecological Information

This material is not expected to cause harm to animals, plants or fish.

Section 13: Disposal Considerations

Waste products are not hazardous and their disposal should be in accordance with local regulations.

Section 14: Transport Information

No special precautions or restrictions involving transport or conveyance of continuous filament E-glass are known to STS Manufacturing Ltd.

Section 15: Regulatory Information

Risk Phrase: R38

Hazard Symbol: Irritant Xi

Safety Phrases: S (2), S36/37

Section 16: References

Health and Safety Executive Guidance Note EH40/98 – Occupational Exposure Limits 1998 (HMSO Publisher)

Control of Substances Hazardous to health (COSHH) Regulations,.

Approved Code of Practice COP29 – Control of Substances Hazardous to Health, Control of Carcinogenic Substances Hazardous to Health regulations 1988

Document HS G27 from the Health and Safety Executive – Substances for use at Work etc.

Health and Safety at Work etc. Act 1974 as amended by the Consumer Protection Act 1987

Chemicals (Hazard Information and Packaging for Supply) – Amendment Regulations 1998 (HSE Books) (CHIP⁹⁸)

Respiratory Protective Equipment - A Practical Guide for Users (ISBN 011 8855220) (HMSO Publisher)

Respiratory Protective Equipment - legislative requirements and lists of HSE approved standards and type approved equipment (ISBN 0 11 885609X) (HMSO)

The foregoing information is believed to be accurate at the time of preparation of this document, and is provided in good faith. However, no warranty or representation with respect to such information is intended or given.