



SAFETY DATA SHEET: BD61 Make It Matt 50 ml (for use with Aerokote catalyst)

Revision date: 01/04/2021

2nd revision date 08/05/2021

Page 1/9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Make It Matt

Product number BD61

1.2. Relevant identified uses of the substance or mixture and uses advised against Identified uses:

Matting agent

1.3. Details of the supplier of the safety data sheet :

Deluxe Materials Ltd., Unit 13, Cufaude Business Park, Cufaude Lane, Bramley, Hampshire RG26 5DL United Kingdom

Email: john@deluxematerials.com

1.4. Emergency telephone number

Tel: +44 (0) 1256 883944 (9.00 - 5.00 office hours only)

Catalyst For A/C products mix 10:1 vol 13900 catalyst

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H336

Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xi;R36. F;R11. R67.

2.2. Label elements

Pictogram



Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.



SAFETY DATA SHEET: BD61 Make It Matt 50 ml (for use with Aerokote catalyst)

Revision date: 01/04/2021

2nd revision date 08/05/2021

Page 2/9

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing vapour/ spray.

P264 Wash contaminated skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/ doctor.

P312 Call a POISON CENTRE/doctor if you feel unwell.

P321 Specific treatment (see medical advice on this label).

P332+P313 If skin irritation occurs: Get medical advice/ attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container in accordance with national regulations.

Contains

BUTYL ACETATE -norm, ISO-BUTANOL, BUTANOL-norm, ETHYL ACETATE, PROPYL ACETATE

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ETHANOL		10-30%
CAS number: 64-17-5		EC number: 200-578-6
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	F+R11	
BUTYL ACETATE -norm		10-30%
CAS number: 123-86-4		EC number: 204-658-1
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 R66 R67	
STOT SE 3 - H336		

SAFETY DATA SHEET: BD61 Make It Matt 50 ml (for use with Aerokote catalyst)

Revision date: 01/04/2021

2nd revision date 08/05/2021

Page 3/9

ISO-BUTANOL		5-10%
CAS number: 78-83-1 EC number: 201-148-0		
Classification Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335, H336	Classification (67/548/EEC or 1999/45/EC) R10 Xi;R37/38,R41 R67	
BUTANOL-norm		1-5%
CAS number: 71-36-3 EC number: 200-751-6		
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335, H336	Classification (67/548/EEC or 1999/45/EC) R10 Xn;R22 Xi;R37/38,R41 R67	
ETHYL ACETATE		1-5%
CAS number: 141-78-6 EC number: 205-500-4		
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC or 1999/45/EC) F;R11 Xi;R36 R66 R67	
PROPYL ACETATE		1-5%
CAS number: 109-60-4 EC number: 203-686-1		
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC or 1999/45/EC) F;R11 Xi;R36 R66 R67	
METHANOL		0.1-1%
CAS number: 67-56-1 EC number: 200-659-6		
Classification Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370	Classification (67/548/EEC or 1999/45/EC) F;R11 T;R23/24/25,R39/23/24/25	

SAFETY DATA SHEET: BD61 Make It Matt 50 ml (for use with Aerokote catalyst)

Revision date: 01/04/2021

2nd revision date 08/05/2021

Page 4/9

PROPAN-2-OL		0.1-1%
CAS number: 67-63-0	EC number: 200-661-7	
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC or 1999/45/EC) F;R11 Xi;R36 R67	
FORMALDEHYDE ...%		0.05-0.1%
CAS number: 50-00-0	EC number: 200-001-8	
Classification Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Carc. 1B - H350 STOT SE 3 - H335	Classification (67/548/EEC or 1999/45/EC) Carc. Cat. 3;R40 T;R23/24/25 C;R34 R43	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Keep affected person away from heat, sparks and flames.
Inhalation	Move affected person to fresh air at once. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention immediately.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

Protective actions during firefighting	Avoid breathing fire gases or vapours. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses.
---	--

SAFETY DATA SHEET: BD61 Make It Matt 50 ml (for use with Aerokote catalyst)

Revision date: 01/04/2021

2nd revision date 08/05/2021

Page 5/9

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Use explosion proof electric equipment.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

ETHANOL

Long-term exposure limit (8-hour TWA): OES 1000 ppm 1920 mg/m³

Short-term exposure limit (15-minute): OES

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): OES 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): OES 200 ppm 966 mg/m³

ISO-BUTANOL

Long-term exposure limit (8-hour TWA): OES 50 ppm 154 mg/m³

Short-term exposure limit (15-minute): OES 75 ppm 231 mg/m³

BUTANOL-norm

Long-term exposure limit (8-hour TWA): OES

Short-term exposure limit (15-minute): OES 50 ppm(Sk) 154 mg/m³(Sk)

ETHYL ACETATE

Long-term exposure limit (8-hour TWA): OES 200 ppm

Short-term exposure limit (15-minute): OES 400 ppm

PROPYL ACETATE

Long-term exposure limit (8-hour TWA): OES 200 ppm 849 mg/m³

Short-term exposure limit (15-minute): OES 250 ppm 1060 mg/m³

METHANOL

Long-term exposure limit (8-hour TWA): OES 200 ppm(Sk) 266 mg/m³(Sk)

Short-term exposure limit (15-minute): OES 250 ppm(Sk) 333 mg/m³(Sk)

PROPAN-2-OL

SAFETY DATA SHEET: BD61 Make It Matt 50 ml (for use with Aerokote catalyst)

Revision date: 01/04/2021

2nd revision date 08/05/2021

Page 6/9

Long-term exposure limit (8-hour TWA): OES 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): OES 500 ppm 1250 mg/m³

FORMALDEHYDE ...%

Long-term exposure limit (8-hour TWA): MEL 2 ppm 2.5 mg/m³

Short-term exposure limit (15-minute): MEL 2 ppm 2.5 mg/m³

Ingredient comments OES = Occupational Exposure Standard.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Use protective gloves.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Flash point < 21°C

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid Avoid heat. Avoid contact with the following materials: Oxidising agents. Reducing agents.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition products Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

SAFETY DATA SHEET: BD61 Make It Matt 50 ml (for use with Aerokote catalyst)

Revision date: 01/04/2021

2nd revision date 08/05/2021

Page 7/9

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 7,524.34

Acute toxicity - dermal

ATE dermal (mg/kg) 45,730.28

Acute toxicity - inhalation

ATE inhalation (gases ppm) 106,703.98

ATE inhalation (vapours mg/l) 457.3

ATE inhalation (dusts/mists mg/l) 76.22

Inhalation Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion May cause discomfort if swallowed.

Skin contact Product has a defatting effect on skin. May cause allergic contact eczema.

Eye contact Irritating to eyes.

SECTION 12: Ecological information

Ecotoxicity Dangerous for the environment if discharged into watercourses.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

UN No. (ADN) 1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT RELATED MATERIAL

Proper shipping name (IMDG) PAINT RELATED MATERIAL

Proper shipping name (ICAO) PAINT RELATED MATERIAL

Proper shipping name (ADN) PAINT RELATED MATERIAL

SAFETY DATA SHEET: BD61 Make It Matt 50 ml (for use with Aerokote catalyst)

Revision date: 01/04/2021

2nd revision date 08/05/2021

Page 8/9

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ICAO packing group	II
ADN packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	2
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). Control of Substances Hazardous to Health Regulations 2002 (as amended).
Guidance	Workplace Exposure Limits EH40. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date 01/04/2021

2nd Revision date

08/05/2021

SAFETY DATA SHEET: BD61 Make It Matt 50 ml (for use with Aerokote catalyst)

Revision date: 01/04/2021

2nd revision date 08/05/2021

Page 9/9

Risk phrases in full

R10 Flammable.
R11 Highly flammable.
R20 Harmful by inhalation.
R20/21 Harmful by inhalation and in contact with skin.
R22 Harmful if swallowed.
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
R34 Causes burns.
R36 Irritating to eyes.
R37 Irritating to respiratory system.
R37/38 Irritating to respiratory system and skin.
R38 Irritating to skin.
R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R40 Limited evidence of a carcinogenic effect.
R41 Risk of serious damage to eyes.
R43 May cause sensitisation by skin contact.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H350 May cause cancer.
H370 Causes damage to organs .