


T32MZ(WC)

R3306GY

Setting manual


By installing the latest software on the T32MZ(WC), you can setting the airplane gyro built-in receiver R3306GY on the T32MZ(WC).

Connection T32MZ(WC) and R3306GY




⚠ CAUTION

- Be sure to connect and disconnect the R3306GY and Transmitter connection cable with the power off.




1. Select "Gyro Setting" on the last page of Airplane Model Menu



2. Select "Start"



Select "Start"
This will download the gyro data to the transmitter.



3. Home screen is displayed


To Basic menu

*Once writing is complete, turn the R3306GY off and then on again. The data for the added functions will be deployed.



*R3306GY data cannot be written to other model.

*Data from other models can not be written to R3306GY .


◆ When copying data from R3306GY-A to R3306GY-B



Connect the R3306GY-A to the transmitter and press [Start]. (Enter the data of A into transmitter)



Connect R3306GY-B to transmitter and press [GY Settings Transfer]. (Put data on A into gyro B)



Home screen

On the home screen, basic information such as gyro operation mode, sensitivity, battery voltage are displayed.

Gyro operation mode / Gyro gain

Displays "AVCS" or "Normal" operation mode and gyro gain of aileron (roll), elevator (pitch) and rudder (yaw) axis.

Model name display


Displays the model name of the loaded data.

Battery voltage

Displays the voltage of the receiver battery connected to R3306GY.


Software version

The software version of the connected R3306GY is displayed.




Basic menu for R3306GY


Home screen




Basic menu



◆ Config




◆ S.BUS basic



Config Page 1 Gyro set mounting direction


Set the mounting direction of gyro. Set mounting direction with reference to figure below.




Config Page 1 WING/TAIL

Set with the wing type/tail type of R3306GY. The wing type/tail type of the transmitter is not used and is normal.

- Turn off the elevon/V-tail mixing on the transmitter side.
- Do not use transmitter sub-trim. Adjust using the gyro neutral offset.
- When using the S.BUS servo, you can also use the neutral offset function of the S.BUS servo setting parameters.



Config Page 1 Servo type



Digital servo

Analog servo

Select the servo type according to the servo to be used.

Digital servo → DG : 285 Hz

Analog servo → AN : 70 Hz

The stability of digital-servo mode of a flight increases in order to perform a high-speed control action.

Config

*The AIL3 and AIL4 items will only be displayed if output settings are enabled from the S.BUS basic menu.


Config Page 2 Gyro direction

It is the direction setting of the gyro. Be careful as it will crash if the direction is reversed.


For dual aileron, dual elevator, and dual rudder aircraft, check the operating direction of each second aileron/elevator/rudder.

Config	Model1	Condit.1	100%	2/9
Gyro Dir				
AIL	Normal	AIL2	Normal	
ELE	Normal	ELE2	Normal	
RUD	Normal	RUD2	Normal	
AIL3	Normal	AIL4	Normal	


Tilt the airplane to the left on the ground and check that the ailerons operate to the right.




Tilt the airplane to the left on the ground and check that the 4-ailerons operate to the right.



Turn the airplane to the right on the ground and check that the rudder operates to the left.



Raise the airplane with its nose upward and check that the elevator operates downward.





* AIL3 and AIL4 settings cannot be set with the button settings on the R3306GY main unit.

Config Page 3 Neutral offset


Config	Model1	Condit.1	100%	3/9
Neutral Offset				
AIL	+0	AIL2	+0	
ELE	+0	ELE2	+0	
RUD	+0	RUD2	+0	
AIL3	+0	AIL4	+0	

Neutral position setting for each servo.




This will move the neutral to the desired position.

* AIL3 and AIL4 settings cannot be set with the button settings on the GYA main unit.




This is the limit setting for each servo. The position of the maximum operation is read into the gyro in the first setting.



* AIL3 and AIL4 settings cannot be set with the button settings on the R3306GY parameter settings.

Aileron example



Config Page 6 Holding Power


It is a function to adjust the posture holding force of the aircraft in AVCS mode.

Decreasing the value weakens the holding power and makes the operation feeling closer to the normal mode.

The current rate numbers C1 to C5 are displayed by operating the channel of the transmitter.


Like the flight condition function of the transmitter, you can set up to 5 different data for the attitude holding force rate of the aircraft in AVCS mode by operating the switch from the transmitter, and switch between them. You can set the holding power rate selector switch to the channel with the AFR function of the transmitter, and set the point for each rate on the AFR point curve to switch. It is also possible to use the flight condition function to work with the flight condition switch.

Config 6



With the switch button, the "holding power" of each rate (C1 to C5) can be displayed and adjusted.


S.BUS Basic 2




By operating the channel of the transmitter, the channel position of the current rate numbers C1 to C5 will be displayed in green.

Display and adjust the current rate numbers C1 to C5 by operating the channel on the transmitter.


When set to SW of DG1 or DG2




Switch channel rate



When set to dial or lever



Channel rate



Config Page 7 4D Flight (Backward flight) Gyro Reverse Mode Adjustment

Page 7 is for setting the gyro reverse mode. This is a special setting for 4D backward flight. Select whether to reverse the control direction of the aileron, elevator, and rudder when flying backward. Normally, when flying backward, the steering direction of all the rudder is reversed, so the control direction of the gyro is also reversed.

Switching between forward (FW) and reverse (BK) uses the same CH12 signal as the holding force. Up from near the midpoint of the throttle stick is forward, and down is reverse.

For details on setting the switching point, please refer to the transmitter settings.

In gyro reverse mode, the gyro controls in the same direction as the aircraft’s tilt. Switch between forward and reverse to check that the gyro control direction changes correctly.

Config 7

ConfigModel1Condit.1100%7/9

4D Flight

C3 / BK

AIL

Normal

ELE

Normal

RUD

Normal

S.BUS Basic 3

SBus BasicModel1Condit.1100%3/4

4D Flight

CH12

C3 / BK

-1000100

BK

Config Page 8 4D Flight (Backward flight) Mode Adjustment

Page 8 is for setting the gyro reverse mode. This is a special setting for 4D backward flight. The AET (BK) and AET (FW) functions estimate the aircraft’s flight attitude during forward and backward transitions and optimize gyro control. If the aircraft’s attitude changes quickly, decrease the value. If the attitude changes slowly, increase the value. The correction values for forward and backward transitions can be set independently. The setting range is 0 to 30. The OPC parameter adjusts the speed when the control amount increases and decreases. The setting range is 0 to 27. The values in the setting example are the standard setting values for SkyLeaf-ST. The optimal value will vary depending on the aircraft characteristics and flight style.

Config 8

ConfigModel1Condit.1100%8/9

4D Flight

C3 / BK

AET(BK)

12

AET(FW)

8

OPC AIL

INC

6

DEC

6

OPC ELE

INC

6

DEC

6

OPC RUD


INC

6

DEC

6


Pages 7-8 are for 4D backward flight settings. For detailed settings, refer to the GYA 4D Flight Setting Manual on the Futaba WEB site.



Reset each Config item. It returns to the initial value.


SBUS Basic menu

Set the CH for each function according to the transmitter to be used. Any unused functions should be set to INH (Inhibited).





The channel of each function can be changed.

Tap to move to the rate switching CH setting page.




Holding Power C2 to C5




ON-OFF channel for auto recovery

⚠ WARNING

① Always verify that the S.BUS function assignments match your transmitter's function (in the FUNCTION menu) assignments. If any changes are made within the transmitter function assignments, then it will also be necessary to make the changes within the S.BUS function assignments. To change the channel, R3306GY and transmitter must be connected.



Tap the CH used for rate switching to select it.





Reset each S.BUS function. It returns to the initial value.

CH setting items for AIL3 and AIL4 are displayed on the final screen of the S.BUS basic setting screen. By setting the operation CH of AIL3 and AIL4, the gyro-controlled signal is output to the corresponding CH of the S.BUS output.

* Match the operation CH and CH setting on the function setting screen on the transmitter side.

* When the AIL3 and AIL4 CH settings are INH, the gyro control is not performed and the data sent from the transmitter is output as is.





This is the channel setting for the switch that turns roll flat ON/OFF.

The roll angle at which roll flat turns ON can be set by the pulse width at the ON position.

(Set using the AFR rate on the transmitter for this setting CH, etc.)

【Roll Flat】

This function keeps only the roll axis horizontal (roll angle 0°).


When used during landing approach, it keeps the roll axis horizontal, making aileron operation easier and allowing you to concentrate on throttle and elevator operation, making landing easier. It also maintains horizontality during inverted flight. The roll angle at which the roll flat function turns on should be set to 10° to 15° during landing, and 15° to 20° during normal flight, for a smooth flight.

Conditions for the roll flat function to be ON (when all of the following conditions are met)

- 1) Roll Flat Switch Channel is set (not INH)
- 2) When the roll flat switch channel is in the - position from neutral when viewed on the transmitter AFR setting screen.
- 3) When the roll flat switch channel operation position is viewed on the AFR setting screen of the transmitter, when the rate value is Wp (%), the roll angle of the aircraft is within Wp/2 (degrees).
- 4) When the aileron stick is in the neutral position.
- 5) When the aircraft pitch angle is $\pm 60^\circ$ or less

【EX.】 When the roll flat switch channel is CH15, if the operating position of CH15 is the AFR rate -50%, the roll angle at which the roll flat function will be turned ON will be within $\pm 25^\circ$


When the Roll Flat Switch Channel is set to an AFR rate of -100% or less, the auto recovery mode operates.



When the roll flat switch channel is in the - rate side from neutral, the roll flat function becomes ACT.

The roll angle at which roll flat is ON is 1/2 the AFR rate of the roll flat switch channel operating position.

【EX.】 When the AFR rate of the roll flat switch channel operating position is -50%, if the roll angle is within $\pm 25^\circ$, the roll flat function is ON.




Reset the S.BUS basic items.
After execution, the items will return to the factory default values.

Tap "Reset" and then "Yes" on the confirmation screen to reset to the initial value.

Air Brake

This function is the same as the air brake function of the transmitter. Two rates, A1 and A2, can be set. (The amount of operation is slightly less than that of the air brake function of the transmitter. It can also be used in AVCS mode where the air brake function of the transmitter cannot be used.)





Roll Flat function works even when the air brake is on.

Air brake mix rate No. display

The air brake can be set to two rates: A1 and A2.

Operation rate (-250 ~ 0 ~ +250)




Setting the operating speed of each servo

Setting range : 0 ~ 27

IN is the operating speed when the air brake mix is turned ON.

OUT is the speed when the air brake mix is turned OFF.

When switching between A1 ⇔ A2, the speed setting of the one that is turned ON (IN side) takes priority.




Air brake Mix ON/OFF CH setting

Setting range: INH, CH1-CH16, DG1, DG2

A1 and A2 rates change with the pulse width of the same CH

Set with AFR on the transmitter



A1 and A2 are in the OFF region (neutral to +rate side)


Area where A1 is ON and A2 is OFF ((neutral to -50% side)

Area where A1 is OFF and A2 is ON (-50% or less)

Camber mixing

This function is equivalent to the camber mixing function of the transmitter.

It can also be used in AVCS mode where the transmitter's camber mixing function cannot be used.



Camber Mix ON/OFF setting

[Display]

INH : Inhibit

OFF : Camber Mix is ACT, but Master CH is not set



ON : Camber Mix is set to ACT and the master channel is also set, but the ON/OFF channel is not set (Mixing is active).

ACT : Camber Mix is set to ACT with both the master channel and the ON/OFF channel set.

Camber Mix operation speed setting (0 to 27)

Mixing OFF ⇒ When ON or when the master CH is operated while ON, it operates at the IN side rate.



Mixing ON ⇒ When OFF, it operates at the OUT side rate



Area where camber switch is ON (-50% or less)

Camber Mix ON/OFF CH setting

Range : INH, CH1-CH16, DG1, DG2



[AIL setting screen transition button]

[ELE setting screen transition button]



AIL Operation Rate (-200 ~ 0 ~ +200)

Up and down sides can be set separately

ELE Operation Rate (-200 ~ 0 ~ +200)

Up and down sides can be set separately